

View Online at <https://aerobasegroup.com/nsn/5945-01-172-9056>

**Thread Class:**

2a single mounting facility

**Thread Direction:**

Right-hand single mounting facility

**Thread Length:**

0.344 inches single mounting facility and 0.395 inches single mounting facility

**Overall Length:**

0.928 inches

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

0.488 inches single mounting facility

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

0.220 inches single mounting facility

**Overall Height:**

0.835 inches

**Overall Width:**

0.800 inches

**Environmental Protection:**

Shock resistant and vibration resistant and hermetic

**Frequency In Hertz:**

60.0 or 400.0

**Winding Quantity:**

2

**Coil Quantity:**

2

**Winding Dc Resistance Rating:**

975.0 ohms all windings

**Duty Type:**

Continuous

**Mounting Facility Type And Quantity:**

2 threaded stud single mounting facility

**Features Provided:**

Latching contacts

**Thready Qty Per Inch (tpi):**

40 single mounting facility

**Thread Size:**

0.112 inches single mounting facility

**Mounting Facility Pattern:**

Diagonal single mounting facility

**Nonpile-up Main Contact Arrangement:**

2 pole, double throw, both positions maintained

**Operating Voltage Rating And Type At Specificationified Temp:**

12.0 volts dc 25 degrees celsius all windings and 18.0 volts dc 125 degrees celsius all windings

**Main Contact Load Current Rating At Maximum Rated Voltage:**

2.0 amperes dc resistive load and 0.15 amperes ac resistive load

**Main Contact Maximum Voltage Rating In Volts:**

115.0 ac and 28.0 dc

**Thread Series Designator:**

Unc single mounting facility

**Terminal Type And Quantity:**

10 wire lead all functions

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A03300