NSN 5945-01-172-9708

Electromagnetic Relay - Page 1 of 2

Overall Length:

0.05 seconds fixed release time



View Online at https://aerobasegroup.com/nsn/5945-01-172-9708

1.718 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
1.396 inches single mounting facility and 1.446 inches single mounting facility
Overall Height:
1.300 inches
Overall Width:
0.515 inches
Mounting Slot Width:
0.150 inches single mounting facility
Case Material:
Metal
Environmental Protection:
Dustproof
Fragility Factor:
Moderately rugged
Frequency In Hertz:
Between 50.0 and 400.0
Winding Quantity:
1
Purpose For Which Designed:
General
Coil Quantity:
1
Duty Type:
Continuous
Arc Quenching Method:
Air
Mounting Facility Type And Quantity:
2 slotted hole single mounting facility
Storage Type:
General purpose warehouse
Features Provided:
Polarized
Mounting Facility Pattern:
In-line single mounting facility
Nonpile-up Main Contact Arrangement:
1 pole, double throw, one position momentary
Operating Current Rating And Type:
24.0 milliamperes ac single winding
Time Delay:

NSN 5945-01-172-9708

Electromagnetic Relay - Page 2 of 2



Operating Voltage Rating And Type At Specificationified Temp:

115.0 volts ac 25 degrees celsius single winding

Main Contact Load Current Rating At Maximum Rated Voltage:

10.0 amperes ac resistive load

Main Contact Maximum Voltage Rating In Volts:

115.0 ac

Terminal Type And Quantity:

5 pin all functions

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A03300