NSN 5945-01-173-1136

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-173-1136

·
Thread Class:
2b single mounting facility
Thread Direction:
Right-hand single mounting facility
Overall Length:
3.390 inches
Center To Center Distance Between Mounting Facilities Parallel To Width:
2.000 inches single mounting facility
Overall Height:
2.720 inches
Overall Width:
2.660 inches
Case Material:
Metal
Environmental Protection:
Hermetic
Fragility Factor:
Moderately rugged
Winding Quantity:
1
Purpose For Which Designed:
General
Coil Quantity:
1
Winding Dc Resistance Rating:
132.0 ohms single winding
Duty Type:
Continuous
Arc Quenching Method:
Air
Mounting Facility Type And Quantity:
3 threaded hole single mounting facility
Storage Type:
General purpose warehouse
Cubic Measure:
24.527 cubic inches
Thready Qty Per Inch (tpi):
32 single mounting facility
Thread Size:

.....

0.164 inches single mounting facility

Mounting Facility Pattern:

Triangle single mounting facility

NSN 5945-01-173-1136

Electromagnetic Relay - Page 2 of 2



Nonpile-up Main Contact Arrangement:

4 pole, double throw, one position momentary

Operating Current Rating And Type:

182.0 milliamperes dc single winding

Center To Center Distance Between Mounting Facilities Parallel To The Altitude Of An Isosceles Triangle:

2.500 inches single mounting facility

Operating Voltage Rating And Type At Specificationified Temp:

28.0 volts dc 25 degrees celsius single winding

Main Contact Load Current Rating At Maximum Rated Voltage:

25.0 amperes ac resistive load and 25.0 amperes dc resistive load

Main Contact Maximum Voltage Rating In Volts:

120.0 ac and 28.0 dc

Thread Series Designator:

Unc single mounting facility

Terminal Type And Quantity:

14 screw all functions

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A03300