NSN 5945-01-174-5409

Electromagnetic Relay - Page 1 of 2



| View Online at https://aerobasegroup.com/nsn/5945-01-174-5409 |
|---|
| Thread Class: |
| 2a single mounting facility |
| Thread Direction: |
| Right-hand single mounting facility |
| Overall Length: |
| 1.531 inches |
| Overall Height: |
| 1.906 inches |
| Overall Width: |
| 1.406 inches |
| Case Material: |
| Plastic |
| Environmental Protection: |
| Dustproof |
| Fragility Factor: |
| Moderately rugged |
| Winding Quantity: |
| 1 |
| Purpose For Which Designed: |
| General |
| Coil Quantity: |
| 1 |
| Winding Dc Resistance Rating: |
| 320.0 ohms single winding |
| Duty Type: |
| Continuous |
| Arc Quenching Method: |
| Air |
| Mounting Facility Type And Quantity: |
| 1 threaded stud single mounting facility |
| Storage Type: |
| General purpose warehouse |

Cubic Measure:

4.103 cubic inches

Thready Qty Per Inch (tpi):

32 single mounting facility

Thread Size:

0.138 inches single mounting facility

Nonpile-up Main Contact Arrangement:

4 pole, double throw, one position momentary

Time Delay:

0.015 seconds fixed operate time

NSN 5945-01-174-5409

Electromagnetic Relay - Page 2 of 2



Operating Voltage Rating And Type At Specificationified Temp:

24.0 volts dc 25 degrees celsius single winding

Main Contact Load Current Rating At Maximum Rated Voltage:

10.0 amperes ac resistive load and 10.0 amperes dc resistive load

Main Contact Maximum Voltage Rating In Volts:

240.0 ac and 28.0 dc

Thread Series Designator:

Unc single mounting facility

Terminal Type And Quantity:

14 quick disconnect, male all functions

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A03300