## NSN 5945-01-175-2826

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-175-2826

Overall Length:				
0.810 inches				
Overall Height:				
0.410 inches				
Overall Width:				
0.410 inches				
Fragility Factor:				
Moderately rugged				
Frequency In Hertz:				
Between 60.0 and 400.0				
Winding Quantity:				
1				
Purpose For Which Designed:				
General				
Coil Quantity:				
1				
Winding Dc Resistance Rating:				
160.0 ohms all windings				
Duty Type:				
Continuous				
Arc Quenching Method:				
Air				
Mounting Facility Type And Quantity:				
1 plug-in terminal single mounting facility				
Storage Type:				
General purpose warehouse				
Nonpile-up Main Contact Arrangement:				
2 pole, double throw, one position momentary				
Criticality Code Justification:				
Feat				
Operating Voltage Rating And Type At Specificationified Temp:				
6.4 volts dc 25 degrees celsius all windings				
Main Contact Load Current Rating At Maximum Rated Voltage:				
2.0 amperes dc resistive load				
Main Contact Maximum Voltage Rating In Volts:				
28.0 dc				
Special Features:				
Failure rate 1.0 percent per 10000 cycles				
Test Data Document:				
81349-mil-r-39016 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification				
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain				

environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

8 wire lead all functions

**Terminal Type And Quantity:** 

## NSN 5945-01-175-2826

Electromagnetic Relay - Page 2 of 2



Spec	ific	ation	Data:
------	------	-------	-------

81349-mil-r-39016/6 government specification

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A03300