NSN 5945-01-175-5065

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-175-5065

view Offinie at https://aerobasegroup.com/r
Thread Class:
2a single mounting facility
Thread Direction:
Right-hand single mounting facility
Overall Length:
0.978 inches
Overall Height:
1.388 inches
Overall Width:
0.734 inches
Case Material:
Plastic
Environmental Protection:
Dustproof
Fragility Factor:
Moderately rugged
Contact Material:
Silver
Contact Surface Treatment:
Gold
William Alliam Ocean City
Winding Quantity:
1
-
1
1 Purpose For Which Designed:
1 Purpose For Which Designed: General
Purpose For Which Designed: General Coil Quantity:
1 Purpose For Which Designed: General Coil Quantity:
1 Purpose For Which Designed: General Coil Quantity: 1 Winding Dc Resistance Rating:
Purpose For Which Designed: General Coil Quantity: Winding Dc Resistance Rating: 700.0 ohms single winding
Purpose For Which Designed: General Coil Quantity: Winding Dc Resistance Rating: 700.0 ohms single winding Duty Type:
Purpose For Which Designed: General Coil Quantity: 1 Winding Dc Resistance Rating: 700.0 ohms single winding Duty Type: Continuous
Purpose For Which Designed: General Coil Quantity: Winding Dc Resistance Rating: 700.0 ohms single winding Duty Type: Continuous Arc Quenching Method:
Purpose For Which Designed: General Coil Quantity: Winding Dc Resistance Rating: 700.0 ohms single winding Duty Type: Continuous Arc Quenching Method: Air
Purpose For Which Designed: General Coil Quantity: Winding Dc Resistance Rating: 700.0 ohms single winding Duty Type: Continuous Arc Quenching Method: Air Mounting Facility Type And Quantity:
Purpose For Which Designed: General Coil Quantity: Winding Dc Resistance Rating: 700.0 ohms single winding Duty Type: Continuous Arc Quenching Method: Air Mounting Facility Type And Quantity: 1 threaded stud single mounting facility
Purpose For Which Designed: General Coil Quantity: Winding Dc Resistance Rating: 700.0 ohms single winding Duty Type: Continuous Arc Quenching Method: Air Mounting Facility Type And Quantity: 1 threaded stud single mounting facility Storage Type:
Purpose For Which Designed: General Coil Quantity: Winding Dc Resistance Rating: 700.0 ohms single winding Duty Type: Continuous Arc Quenching Method: Air Mounting Facility Type And Quantity: 1 threaded stud single mounting facility Storage Type: General purpose warehouse
Purpose For Which Designed: General Coil Quantity: Winding Dc Resistance Rating: 700.0 ohms single winding Duty Type: Continuous Arc Quenching Method: Air Mounting Facility Type And Quantity: 1 threaded stud single mounting facility Storage Type: General purpose warehouse Cubic Measure:
Purpose For Which Designed: General Coil Quantity: 1 Winding Dc Resistance Rating: 700.0 ohms single winding Duty Type: Continuous Arc Quenching Method: Air Mounting Facility Type And Quantity: 1 threaded stud single mounting facility Storage Type: General purpose warehouse Cubic Measure: 0.817 cubic inches

0.099 inches single mounting facility

NSN 5945-01-175-5065

Electromagnetic Relay - Page 2 of 2



Nonpile-up Main Contact Arrangement:

2 pole, double throw, one position momentary

Operating Voltage Rating And Type At Specificationified Temp:

24.0 volts dc 25 degrees celsius single winding

Main Contact Load Current Rating At Maximum Rated Voltage:

3.0 amperes ac resistive load and 3.0 amperes dc resistive load

Main Contact Maximum Voltage Rating In Volts:

120.0 ac and 32.0 dc

Energizing Element Power Rating:

1.0 watts

Precious Material And Location:

Contacts silver and contacts surfaces gold

Precious Material:

Silver and gold

Thread Series Designator:

Unc single mounting facility

Terminal Type And Quantity:

8 tab, solder lug all functions

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A03300