# NSN 5945-01-177-2081

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-177-2081

# Thread Class:

2a single mounting facility

**Thread Direction:** 

Right-hand single mounting facility

### Thread Length:

0.270 inches single mounting facility

#### **Overall Length:**

1.110 inches

#### **Overall Height:**

1.590 inches

**Overall Width:** 

0.520 inches

#### **Case Material:**

Plastic

#### Environmental Protection:

Dustproof

# Fragility Factor:

Moderately rugged

# Contact Material:

Silver

## Contact Surface Treatment:

Gold flash

#### **Frequency In Hertz:**

60.0

# Winding Quantity:

1

### Purpose For Which Designed:

General

### **Coil Quantity:**

1

# Duty Type:

Continuous

# Arc Quenching Method:

Air

# Mounting Facility Type And Quantity:

1 threaded stud single mounting facility

### Storage Type:

General purpose warehouse

#### **Cubic Measure:**

0.918 cubic inches

# Thready Qty Per Inch (tpi):

48 single mounting facility

# NSN 5945-01-177-2081

Electromagnetic Relay - Page 2 of 2

**Thread Size:** 0.099 inches single mounting facility **Nonpile-up Main Contact Arrangement:** 4 pole, double throw, one position momentary **Time Delay:** 0.013 seconds fixed operate time **Operating Voltage Rating And Type At Specificationified Temp:** 115.0 volts ac 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage: 5.0 amperes ac resistive load and 5.0 amperes dc resistive load Main Contact Maximum Voltage Rating In Volts: 240.0 ac and 28.0 dc **Energizing Element Power Rating:** 1.2 volts-amperes **Precious Material And Location:** Contacts silver and contact surfaces gold **Precious Material:** Gold and silver **Thread Series Designator:** Unc single mounting facility **Terminal Type And Quantity:** 14 tab, solder lug all functions Shelf Life: N/a Unit Of Measure: ---**Demilitarization:** No Fiig: A03300

