## NSN 5945-01-177-2289

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-177-2289

30.0 amperes ac resistive load and 30.0 amperes dc resistive load

Overall Length:
6.000 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
5.438 inches single mounting facility
Overall Height:
2.500 inches
Overall Width:
2.500 inches
Case Material:
Metal
Environmental Protection:
Hermetic
Unthreaded Mounting Hole Diameter:
0.173 inches single mounting facility
Fragility Factor:
Moderately rugged
Frequency In Hertz:
60.0
Winding Quantity:
1
Purpose For Which Designed:
General
Coil Quantity:
1
Duty Type:
Continuous
Arc Quenching Method:
Air
Mounting Facility Type And Quantity:
2 unthreaded hole single mounting facility
Storage Type:
General purpose warehouse
Cubic Measure:
37.500 cubic inches
Mounting Facility Pattern:
In-line single mounting facility
Nonpile-up Main Contact Arrangement:
2 pole, single throw, normally open, momentary action and 2 pole, single throw, normally closed, momentary action
Operating Voltage Rating And Type At Specificationified Temp:
440.0 volts ac 25 degrees celsius single winding
Main Contact Load Current Rating At Maximum Rated Voltage:

## NSN 5945-01-177-2289

Electromagnetic Relay - Page 2 of 2



Main Contact	Maximum	Voltage	Rating	In	Volts:
mam oomas				•••	

440.0 ac and 230.0 dc

**Terminal Type And Quantity:** 

10 screw all functions

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A03300