## NSN 5945-01-177-2803

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-177-2803

Thread Class:
2a single mounting facility
Thread Direction:
Right-hand single mounting facility
Overall Length:
1.625 inches
Center To Center Distance Between Mounting Facilities Parallel To Width:
0.500 inches single mounting facility
Overall Height:
2.375 inches
Overall Width:
1.000 inches
Case Material:
Metal
Environmental Protection:
Dustproof
Fragility Factor:
Moderately rugged
Winding Quantity:
1
Purpose For Which Designed:
Purpose For Which Designed: General
· · ·
General
General  Coil Quantity:
General  Coil Quantity: 1
General  Coil Quantity:  1  Winding Dc Resistance Rating:
General  Coil Quantity:  1  Winding Dc Resistance Rating:  2.5 kilohms single winding
General  Coil Quantity:  1  Winding Dc Resistance Rating:  2.5 kilohms single winding  Duty Type:
General  Coil Quantity:  1  Winding Dc Resistance Rating:  2.5 kilohms single winding  Duty Type:  Continuous
General  Coil Quantity:  1  Winding Dc Resistance Rating:  2.5 kilohms single winding  Duty Type:  Continuous  Arc Quenching Method:
General  Coil Quantity:  1  Winding Dc Resistance Rating:  2.5 kilohms single winding  Duty Type:  Continuous  Arc Quenching Method:  Air
General  Coil Quantity:  1  Winding Dc Resistance Rating: 2.5 kilohms single winding  Duty Type:  Continuous  Arc Quenching Method:  Air  Mounting Facility Type And Quantity:
General  Coil Quantity:  1  Winding Dc Resistance Rating:  2.5 kilohms single winding  Duty Type:  Continuous  Arc Quenching Method:  Air  Mounting Facility Type And Quantity:  3 threaded stud single mounting facility
General  Coil Quantity:  1  Winding Dc Resistance Rating:  2.5 kilohms single winding  Duty Type:  Continuous  Arc Quenching Method:  Air  Mounting Facility Type And Quantity:  3 threaded stud single mounting facility  Storage Type:
General  Coil Quantity:  1  Winding Dc Resistance Rating: 2.5 kilohms single winding  Duty Type: Continuous  Arc Quenching Method: Air  Mounting Facility Type And Quantity: 3 threaded stud single mounting facility  Storage Type: General purpose warehouse
General  Coil Quantity:  1  Winding Dc Resistance Rating: 2.5 kilohms single winding  Duty Type: Continuous  Arc Quenching Method: Air  Mounting Facility Type And Quantity: 3 threaded stud single mounting facility  Storage Type: General purpose warehouse  Cubic Measure:
General  Coil Quantity:  1  Winding Dc Resistance Rating: 2.5 kilohms single winding  Duty Type: Continuous  Arc Quenching Method: Air  Mounting Facility Type And Quantity: 3 threaded stud single mounting facility  Storage Type: General purpose warehouse  Cubic Measure: 3.859 cubic inches
Coil Quantity:  1 Winding Dc Resistance Rating: 2.5 kilohms single winding Duty Type: Continuous Arc Quenching Method: Air Mounting Facility Type And Quantity: 3 threaded stud single mounting facility Storage Type: General purpose warehouse Cubic Measure: 3.859 cubic inches Thready Qty Per Inch (tpi):

**Mounting Facility Pattern:** 

Triangle single mounting facility

## NSN 5945-01-177-2803

Electromagnetic Relay - Page 2 of 2



## **Nonpile-up Main Contact Arrangement:**

4 pole, double throw, one position momentary

Center To Center Distance Between Mounting Facilities Parallel To The Altitude Of An Isosceles Triangle:

1.350 inches single mounting facility

**Operating Voltage Rating And Type At Specificationified Temp:** 

48.0 volts dc 25 degrees celsius single winding

Main Contact Load Current Rating At Maximum Rated Voltage:

5.0 amperes ac resistive load

**Main Contact Maximum Voltage Rating In Volts:** 

115.0 ac

**Thread Series Designator:** 

Unc single mounting facility

**Terminal Type And Quantity:** 

14 wire hook all functions

Shelf Life:

N/a

**Unit Of Measure:** 

--

**Demilitarization:** 

No

Fiig:

A03300