# NSN 5945-01-177-2803

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-177-2803

# Thread Class:

2a single mounting facility

## **Thread Direction:**

Right-hand single mounting facility

## **Overall Length:**

1.625 inches

### Center To Center Distance Between Mounting Facilities Parallel To Width:

0.500 inches single mounting facility

#### **Overall Height:**

2.375 inches

**Overall Width:** 

1.000 inches

#### **Case Material:**

Metal

### Environmental Protection:

Dustproof

## Fragility Factor:

Moderately rugged

# Winding Quantity:

1

## Purpose For Which Designed:

General

### **Coil Quantity:**

1

# Winding Dc Resistance Rating:

2.5 kilohms single winding

# Duty Type:

Continuous

# Arc Quenching Method:

Air

# Mounting Facility Type And Quantity:

3 threaded stud single mounting facility

# Storage Type:

General purpose warehouse

# Cubic Measure:

3.859 cubic inches

# Thready Qty Per Inch (tpi):

40 single mounting facility

# Thread Size:

0.112 inches single mounting facility

# Mounting Facility Pattern:

Triangle single mounting facility

# NSN 5945-01-177-2803

Electromagnetic Relay - Page 2 of 2



Nonpile-up Main Contact Arrangement: 4 pole, double throw, one position momentary Center To Center Distance Between Mounting Facilities Parallel To The Altitude Of An Isosceles Triangle: 1.350 inches single mounting facility **Operating Voltage Rating And Type At Specificationified Temp:** 48.0 volts dc 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage: 5.0 amperes ac resistive load Main Contact Maximum Voltage Rating In Volts: 115.0 ac **Thread Series Designator:** Unc single mounting facility **Terminal Type And Quantity:** 14 wire hook all functions Shelf Life: N/a Unit Of Measure: ---**Demilitarization:** No Fiig: A03300