NSN 5945-01-177-5207

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-177-5207

Overall Length: 6.125 inches Center To Center Distance Between Mounting Facilities Parallel To Length: 3.750 inches single mounting facility Center To Center Distance Between Mounting Facilities Parallel To Width: 2.500 inches single mounting facility Overall Height: 4.750 inches Overall Width:
Center To Center Distance Between Mounting Facilities Parallel To Length: 3.750 inches single mounting facility Center To Center Distance Between Mounting Facilities Parallel To Width: 2.500 inches single mounting facility Overall Height: 4.750 inches
3.750 inches single mounting facility Center To Center Distance Between Mounting Facilities Parallel To Width: 2.500 inches single mounting facility Overall Height: 4.750 inches
Center To Center Distance Between Mounting Facilities Parallel To Width: 2.500 inches single mounting facility Overall Height: 4.750 inches
2.500 inches single mounting facility Overall Height: 4.750 inches
Overall Height: 4.750 inches
4.750 inches
Overall Width
Overall Width.
2.875 inches
Case Material:
Metal
Environmental Protection:
Dustproof
Unthreaded Mounting Hole Diameter:
0.219 inches single mounting facility
Fragility Factor:
Moderately rugged
Frequency In Hertz:
60.0
Winding Quantity:
1
Purpose For Which Designed:
General
Coil Quantity:
1
Duty Type:
Continuous
Arc Quenching Method:
Air
Mounting Facility Type And Quantity:
4 unthreaded hole single mounting facility
Storage Type:
General purpose warehouse
Cubic Measure:
83.644 cubic inches
Mounting Facility Pattern:
Rectangular single mounting facility
Nonpile-up Main Contact Arrangement:
5 pole, single throw, normally open, momentary action

Time Delay:

0.05 seconds fixed operate and release time

NSN 5945-01-177-5207

Electromagnetic Relay - Page 2 of 2



Operating	Voltage	Rating	And '	Type At	Specifi	cationified	Temp:

440.0 volts ac 25 degrees celsius single winding

Main Contact Load Current Rating At Maximum Rated Voltage:

15.0 amperes ac resistive load

Main Contact Maximum Voltage Rating In Volts:

440.0 ac

Terminal Type And Quantity:

12 screw all functions

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A03300