

View Online at <https://aerobasegroup.com/nsn/5945-01-180-1133>

**Overall Length:**

0.370 inches

**Overall Height:**

0.275 inches

**Overall Width:**

0.370 inches

**Environmental Protection:**

Hermetic

**Winding Quantity:**

1

**Coil Quantity:**

1

**Winding Dc Resistance Rating:**

880.0 ohms single winding

**Duty Type:**

Continuous

**Mounting Facility Type And Quantity:**

1 terminal single mounting facility

**Features Provided:**

Polarized and coil voltage suppression

**Nonpile-up Main Contact Arrangement:**

2 pole, double throw, one position momentary

**Operating Current Rating And Type:**

22.1 milliamperes dc single winding

**Criticality Code Justification:**

Feat

**Time Delay:**

0.004 seconds fixed release time

**Operating Voltage Rating And Type At Specificationified Temp:**

18.0 volts dc 25 degrees celsius single winding

**Main Contact Load Current Rating At Maximum Rated Voltage:**

100.0 milliamperes dc lamp load

**Main Contact Maximum Voltage Rating In Volts:**

28.0 dc

**Special Features:**

Failure rate level 0.1 percent

**Test Data Document:**

81349-mil-r-39016 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Terminal Type And Quantity:**

8 wire lead all functions

**Specification Data:**

81349-mil-r-39016/19 government specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A03300