

View Online at <https://aerobasegroup.com/nsn/5945-01-181-4011>

Thread Class:

2a single mounting facility

Thread Direction:

Right-hand single mounting facility

Thread Length:

0.171 inches single mounting facility

Overall Length:

1.010 inches

Center To Center Distance Between Mounting Facilities Parallel To Width:

0.354 inches single mounting facility

Overall Height:

1.710 inches

Overall Width:

0.735 inches

Environmental Protection:

Dustproof

Fragility Factor:

Moderately rugged

Contact Material:

Silver

Contact Surface Treatment:

Gold flash

Winding Quantity:

1

Purpose For Which Designed:

General

Coil Quantity:

1

Winding Dc Resistance Rating:

2.3 kilohms single winding and 2.8 kilohms single winding

Duty Type:

Continuous

Arc Quenching Method:

Air

Mounting Facility Type And Quantity:

2 threaded stud single mounting facility

Storage Type:

General purpose warehouse

Cubic Measure:

1.269 cubic inches

Thready Qty Per Inch (tpi):

48 single mounting facility

Thread Size:

0.099 inches single mounting facility

Mounting Facility Pattern:

In-line single mounting facility

Nonpile-up Main Contact Arrangement:

2 pole, double throw, one position momentary

Operating Voltage Rating And Type At Specificationified Temp:

12.0 volts dc 25 degrees celsius single winding

Main Contact Load Current Rating At Maximum Rated Voltage:

410.0 milliamperes dc resistive load

Main Contact Maximum Voltage Rating In Volts:

12.0 dc

Precious Material And Location:

Terminals silver and terminal surfaces gold

Thread Series Designator:

Unc single mounting facility

Terminal Type And Quantity:

10 tab, solder lug all functions

Specification Data:

98747-7822228-007 manufacturers specification control

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A03300