NSN 5945-01-181-8879

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-181-8879

| Overall Length: |
|---|
| 1.656 inches |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 1.406 inches single mounting facility |
| Overall Height: |
| 1.687 inches |
| Overall Width: |
| 1.125 inches |
| Case Material: |
| Metal |
| Environmental Protection: |
| Hermetic |
| Unthreaded Mounting Hole Diameter: |
| 0.144 inches single mounting facility |
| Fragility Factor: |
| Moderately rugged |
| Winding Quantity: |
| 1 |
| Purpose For Which Designed: |
| General |
| Coil Quantity: |
| 1 |
| Winding Dc Resistance Rating: |
| 1.0 kilohms single winding |
| Duty Type: |
| Continuous |
| Arc Quenching Method: |
| Air |
| Mounting Facility Type And Quantity: |
| 2 unthreaded hole single mounting facility |
| Storage Type: |
| General purpose warehouse |
| Cubic Measure: |
| 3.143 cubic inches |
| Mounting Facility Pattern: |
| In-line single mounting facility |
| Nonpile-up Main Contact Arrangement: |
| 4 pole, double throw, one position momentary |
| Time Delay: |
| 0.01 seconds fixed operate time |
| Operating Voltage Rating And Type At Specificationified Temp: |
| 48.0 volts dc 25 degrees celsius single winding |

NSN 5945-01-181-8879

Electromagnetic Relay - Page 2 of 2



Main Contact Load Current Rating At Maximum Rated Voltage:

2.0 amperes ac resistive load and 5.0 amperes dc resistive load

Main Contact Maximum Voltage Rating In Volts:

115.0 ac and 29.0 dc

Terminal Type And Quantity:

14 pin all functions

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A03300