# NSN 5945-01-181-8992

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-181-8992

# **Overall Length:**

Between 1.320 inches and 1.330 inches

## Center To Center Distance Between Mounting Facilities Parallel To Length:

1.057 inches single mounting facility and 1.067 inches single mounting facility

# Center To Center Distance Between Mounting Facilities Parallel To Width:

0.276 inches single mounting facility and 0.286 inches single mounting facility

#### **Overall Height:**

Between 0.450 inches and 0.460 inches

#### **Overall Width:**

Between 0.890 inches and 0.900 inches

#### **Environmental Protection:**

Hermetic

#### **Unthreaded Mounting Hole Diameter:**

0.115 inches single mounting facility and 0.125 inches single mounting facility

#### Fragility Factor:

Moderately rugged

# Winding Quantity:

1

# **Purpose For Which Designed:**

General

# **Coil Quantity:**

1

# Winding Dc Resistance Rating:

540.0 ohms single winding and 660.0 ohms single winding

#### **Duty Type:**

Continuous

#### Arc Quenching Method:

Air

# Mounting Facility Type And Quantity:

4 unthreaded hole single mounting facility

#### Storage Type:

General purpose warehouse

#### **Cubic Measure:**

0.540 cubic inches

#### **Mounting Facility Pattern:**

Rectangular single mounting facility

#### Nonpile-up Main Contact Arrangement:

2 pole, double throw, one position momentary

#### Time Delay:

0.005 seconds fixed operate time

#### **Operating Voltage Rating And Type At Specificationified Temp:**

26.5 volts dc 25 degrees celsius single winding

# NSN 5945-01-181-8992

Electromagnetic Relay - Page 2 of 2



# Main Contact Load Current Rating At Maximum Rated Voltage:

1.0 amperes dc inductive load

# Main Contact Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

# Terminal Type And Quantity:

8 wire hook all functions

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A03300