

View Online at <https://aerobasegroup.com/nsn/5945-01-183-7948>

Thread Class:

2a single mounting facility

Thread Direction:

Right-hand single mounting facility

Overall Length:

3.400 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

0.625 inches single mounting facility

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.200 inches single mounting facility

Overall Height:

3.300 inches

Overall Width:

2.100 inches

Environmental Protection:

Hermetic and vibration resistant

Frequency In Hertz:

400.0

Winding Quantity:

1

Coil Quantity:

1

Duty Type:

Continuous

Mounting Facility Type And Quantity:

4 threaded stud single mounting facility

Thread Size:

0.190 inches single mounting facility

Nonpile-up Main Contact Arrangement:

1 two circuit, double break/double make, one position momentary

Operating Current Rating And Type:

0.6 amperes dc single winding

Nonpile-up Auxiliary Contact Arrangement:

2 two circuit, double break/double make, one position momentary

Auxiliary Contact Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Operating Voltage Rating And Type At Specificationified Temp:

28.0 volts dc 25 degrees celsius single winding

Main Contact Load Current Rating At Maximum Rated Voltage:

20.0 amperes dc motor load

Main Contact Maximum Voltage Rating In Volts:

28.0 dc

Auxiliary Contact Load Current Rating At Maximum Rated Voltage:

5.0 amperes ac resistive load and 5.0 amperes dc resistive load

Thread Series Designator:

Unc single mounting facility

Terminal Type And Quantity:

9 pin energizing element

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiiig:

A03300