# NSN 5945-01-186-6346

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-186-6346

## Thread Class:

2a second mounting facility

### **Thread Direction:**

Right-hand second mounting facility

### Thread Length:

0.375 inches second mounting facility

#### **Overall Length:**

1.616 inches

#### **Overall Height:**

1.593 inches

**Overall Width:** 

0.910 inches

#### **Case Material:**

Metal

#### Environmental Protection:

Hermetic

#### **Fragility Factor:**

Moderately rugged

### **Contact Material:**

Silver

## Winding Quantity:

1

## Purpose For Which Designed:

General

## **Coil Quantity:**

1

## Duty Type:

Continuous

## Arc Quenching Method:

Air

# Mounting Facility Type And Quantity:

1 threaded stud second mounting facility

# Storage Type:

General purpose warehouse

# Thready Qty Per Inch (tpi):

48 first mounting facility

# Thread Size:

0.138 inches second mounting facility

# Nonpile-up Main Contact Arrangement:

4 pole, double throw, one position momentary

# Time Delay:

0.013 seconds fixed operate time

# NSN 5945-01-186-6346

Electromagnetic Relay - Page 2 of 2



**Operating Voltage Rating And Type At Specificationified Temp:** 34.0 volts dc 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage: 3.0 amperes ac resistive load and 3.0 amperes dc resistive load Main Contact Maximum Voltage Rating In Volts: 120.0 ac and 30.0 dc **Energizing Element Power Rating:** 900.0 milliwatts **Precious Material And Location:** Contacts silver **Precious Material:** Silver **Thread Series Designator:** Unc second mounting facility **Terminal Type And Quantity:** 14 tab, solder lug all functions Shelf Life: N/a Unit Of Measure: ---**Demilitarization:** No Fiig: A03300