NSN 5945-01-188-2258

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-188-2258

| Overall Length |
|---|
| Overall Length: 2.625 inches |
| |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 2.125 inches single mounting facility |
| Center To Center Distance Between Mounting Facilities Parallel To Width: |
| 2.125 inches single mounting facility |
| Overall Height: |
| 3.130 inches |
| Overall Width: |
| 2.625 inches |
| Case Material: |
| Metal |
| Environmental Protection: |
| Hermetic |
| Unthreaded Mounting Hole Diameter: |
| 0.196 inches single mounting facility |
| Fragility Factor: |
| Moderately rugged |
| Winding Quantity: |
| 1 |
| Purpose For Which Designed: |
| General |
| Coil Quantity: |
| 1 Winding De Besistance Betimes |
| Winding Dc Resistance Rating: |
| 76.0 ohms single winding |
| Duty Type: |
| Continuous |
| Arc Quenching Method: |
| Air |
| Mounting Facility Type And Quantity: |
| 4 unthreaded hole single mounting facility |
| Storage Type: |
| General purpose warehouse |
| Cubic Measure: |
| 21.567 cubic inches |
| Mounting Facility Pattern: |
| Rectangular single mounting facility |
| Nonpile-up Main Contact Arrangement: |
| 4 pole, double throw, one position momentary |

Time Delay:

0.015 seconds fixed operate and release time

NSN 5945-01-188-2258

Electromagnetic Relay - Page 2 of 2



Operating Voltage Rating And Type At Specificationified Temp:

24.0 volts dc 25 degrees celsius single winding

Main Contact Load Current Rating At Maximum Rated Voltage:

1.0 amperes ac resistive load and 3.0 amperes dc resistive load

Main Contact Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Terminal Type And Quantity:

14 tab, solder lug all functions

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A03300