

View Online at <https://aerobasegroup.com/nsn/5945-01-188-4819>

Overall Length:

1.730 inches

Overall Height:

2.110 inches

Overall Width:

1.280 inches

Environmental Protection:

Hermetic

Unthreaded Mounting Hole Diameter:

0.150 inches single mounting facility

Frequency In Hertz:

400.0

Winding Quantity:

1

Coil Quantity:

1

Duty Type:

Continuous

Mounting Facility Type And Quantity:

3 unthreaded hole single mounting facility

Mounting Facility Pattern:

Triangle single mounting facility

Nonpile-up Main Contact Arrangement:

2 pole, double throw, one position momentary

Operating Current Rating And Type:

150.0 milliamperes dc single winding

Time Delay:

160.00 seconds fixed operate time

Center To Center Distance Between Mounting Facilities Parallel To The Altitude Of An Isosceles Triangle:

1.446 inches single mounting facility

Operating Voltage Rating And Type At Specificationified Temp:

28.0 volts dc 25 degrees celsius single winding

Main Contact Load Current Rating At Maximum Rated Voltage:

8.0 amperes ac inductive load and 8.0 amperes dc inductive load

Main Contact Maximum Voltage Rating In Volts:

200.0 ac and 28.0 dc

Test Data Document:

81349-mil-r-83726 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

8 wire hook all functions

Specification Data:

81349-mil-r-83726/3 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A03300