NSN 5945-01-189-5123

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-189-5123

Overall Length:
3.635 inches
Center To Center Distance Between Mounting Facilities Parallel To Width:
1.875 inches single mounting facility
Overall Height:
2.280 inches
Overall Width:
2.500 inches
Environmental Protection:
Fungus resistant
Unthreaded Mounting Hole Diameter:
0.187 inches single mounting facility
Fragility Factor:
Moderately rugged
Contact Material:
Silver
Contact Surface Treatment:
Gold flash
Winding Quantity:
1
Purpose For Which Designed:
General
General Coil Quantity:
Coil Quantity:
Coil Quantity:
Coil Quantity: 1 Duty Type:
Coil Quantity: 1 Duty Type: Continuous
Coil Quantity: 1 Duty Type: Continuous Arc Quenching Method:
Coil Quantity: 1 Duty Type: Continuous Arc Quenching Method: Magnetic
Coil Quantity: 1 Duty Type: Continuous Arc Quenching Method: Magnetic Mounting Facility Type And Quantity:
Coil Quantity: 1 Duty Type: Continuous Arc Quenching Method: Magnetic Mounting Facility Type And Quantity: 2 unthreaded hole single mounting facility
Coil Quantity: 1 Duty Type: Continuous Arc Quenching Method: Magnetic Mounting Facility Type And Quantity: 2 unthreaded hole single mounting facility Storage Type:
Coil Quantity: 1 Duty Type: Continuous Arc Quenching Method: Magnetic Mounting Facility Type And Quantity: 2 unthreaded hole single mounting facility Storage Type: General purpose warehouse
Coil Quantity: 1 Duty Type: Continuous Arc Quenching Method: Magnetic Mounting Facility Type And Quantity: 2 unthreaded hole single mounting facility Storage Type: General purpose warehouse Mounting Facility Pattern:
Coil Quantity: 1 Duty Type: Continuous Arc Quenching Method: Magnetic Mounting Facility Type And Quantity: 2 unthreaded hole single mounting facility Storage Type: General purpose warehouse Mounting Facility Pattern: In-line single mounting facility
Coil Quantity: 1 Duty Type: Continuous Arc Quenching Method: Magnetic Mounting Facility Type And Quantity: 2 unthreaded hole single mounting facility Storage Type: General purpose warehouse Mounting Facility Pattern: In-line single mounting facility Nonpile-up Main Contact Arrangement:
Coil Quantity: 1 Duty Type: Continuous Arc Quenching Method: Magnetic Mounting Facility Type And Quantity: 2 unthreaded hole single mounting facility Storage Type: General purpose warehouse Mounting Facility Pattern: In-line single mounting facility Nonpile-up Main Contact Arrangement: 1 pole, single throw, normally open, double make, momentary action
Coil Quantity: 1 Duty Type: Continuous Arc Quenching Method: Magnetic Mounting Facility Type And Quantity: 2 unthreaded hole single mounting facility Storage Type: General purpose warehouse Mounting Facility Pattern: In-line single mounting facility Nonpile-up Main Contact Arrangement: 1 pole, single throw, normally open, double make, momentary action Operating Current Rating And Type:

250.0 ac and 250.0 dc

Auxiliary Contact Maximum Voltage Rating In Volts:

NSN 5945-01-189-5123

Electromagnetic Relay - Page 2 of 2

No Fiig: A03300



Operating Voltage Rating And Type At Specificationified Temp: 24.0 volts dc 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage: 2.0 amperes dc resistive load **Main Contact Maximum Voltage Rating In Volts:** 500.0 dc **Auxiliary Contact Load Current Rating At Maximum Rated Voltage:** 10.0 probe ac resistive load and 250.0 dual 16 stage dc resistive load **Energizing Element Power Rating:** 2.0 watts **Precious Material And Location:** Contacts silver and contact surfaces gold **Precious Material:** Gold and silver **Terminal Type And Quantity:** 10 screw all functions Shelf Life: N/a **Unit Of Measure: Demilitarization:**