NSN 5945-01-189-5123

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-189-5123

Overall Length: 3.635 inches Center To Center Distance Between Mounting Facilities Parallel To Width: 1.875 inches single mounting facility **Overall Height:** 2.280 inches **Overall Width:** 2.500 inches **Environmental Protection:** Fungus resistant **Unthreaded Mounting Hole Diameter:** 0.187 inches single mounting facility **Fragility Factor:** Moderately rugged **Contact Material:** Silver **Contact Surface Treatment:** Gold flash Winding Quantity: 1 **Purpose For Which Designed:** General **Coil Quantity:** 1 **Duty Type:** Continuous Arc Quenching Method: Magnetic Mounting Facility Type And Quantity: 2 unthreaded hole single mounting facility Storage Type: General purpose warehouse **Mounting Facility Pattern:** In-line single mounting facility Nonpile-up Main Contact Arrangement: 1 pole, single throw, normally open, double make, momentary action **Operating Current Rating And Type:** 84.0 milliamperes dc single winding Nonpile-up Auxiliary Contact Arrangement: 2 pole, double throw, one position momentary Auxiliary Contact Maximum Voltage Rating In Volts: 250.0 ac and 250.0 dc

NSN 5945-01-189-5123

Electromagnetic Relay - Page 2 of 2



Operating Voltage Rating And Type At Specificationified Temp: 24.0 volts dc 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage: 2.0 amperes dc resistive load Main Contact Maximum Voltage Rating In Volts: 500.0 dc Auxiliary Contact Load Current Rating At Maximum Rated Voltage: 10.0 probe ac resistive load and 250.0 dual 16 stage dc resistive load **Energizing Element Power Rating:** 2.0 watts **Precious Material And Location:** Contacts silver and contact surfaces gold **Precious Material:** Gold and silver **Terminal Type And Quantity:** 10 screw all functions Shelf Life: N/a Unit Of Measure: ---**Demilitarization:** No Fiig: A03300