## NSN 5945-01-190-6832

Electrical Solenoid - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-190-6832

Thread Class:
2b mounting facility hole
Thread Direction:
Right-hand mounting facility hole
Body Style:
Cylindrical frame
Body Diameter:
0.375 inches
Body Length:
0.968 inches
Case Material:
Metal
Maximum Operating Temp:
71.0 degrees celsius
Fragility Factor:
Moderately rugged
Actuator Diameter:
0.075 inches
Inclosure Type:
Fully enclosed
Magnetic Coil Quantity:
1
1 Electrical Resistance:
Electrical Resistance:
Electrical Resistance: 300.00 ohms
Electrical Resistance: 300.00 ohms Duty Type:
Electrical Resistance: 300.00 ohms  Duty Type: Continuous
Electrical Resistance: 300.00 ohms  Duty Type: Continuous  Terminal Location:
Electrical Resistance: 300.00 ohms  Duty Type: Continuous  Terminal Location: Circumference
Electrical Resistance: 300.00 ohms  Duty Type: Continuous  Terminal Location: Circumference Voltage Rating In Volts:
Electrical Resistance: 300.00 ohms  Duty Type: Continuous  Terminal Location: Circumference  Voltage Rating In Volts: 15.0 dc
Electrical Resistance: 300.00 ohms  Duty Type: Continuous  Terminal Location: Circumference Voltage Rating In Volts: 15.0 dc  Mounting Facility Type And Quantity:
Electrical Resistance: 300.00 ohms  Duty Type: Continuous  Terminal Location: Circumference  Voltage Rating In Volts: 15.0 dc  Mounting Facility Type And Quantity: 1 threaded hole
Electrical Resistance: 300.00 ohms  Duty Type: Continuous  Terminal Location: Circumference  Voltage Rating In Volts: 15.0 dc  Mounting Facility Type And Quantity: 1 threaded hole  Storage Type:
Electrical Resistance: 300.00 ohms  Duty Type: Continuous  Terminal Location: Circumference Voltage Rating In Volts: 15.0 dc  Mounting Facility Type And Quantity: 1 threaded hole  Storage Type: General purpose warehouse
Electrical Resistance: 300.00 ohms  Duty Type: Continuous  Terminal Location: Circumference Voltage Rating In Volts: 15.0 dc  Mounting Facility Type And Quantity: 1 threaded hole  Storage Type: General purpose warehouse Thready Qty Per Inch (tpi):
Electrical Resistance: 300.00 ohms  Duty Type: Continuous  Terminal Location: Circumference  Voltage Rating In Volts: 15.0 dc  Mounting Facility Type And Quantity: 1 threaded hole  Storage Type: General purpose warehouse Thready Qty Per Inch (tpi): 56 mounting facility hole
Electrical Resistance: 300.00 ohms  Duty Type: Continuous  Terminal Location: Circumference Voltage Rating In Volts: 15.0 dc  Mounting Facility Type And Quantity: 1 threaded hole Storage Type: General purpose warehouse Thready Qty Per Inch (tpi): 56 mounting facility hole Actuator Stroke Type:
Electrical Resistance: 300.00 ohms  Duty Type: Continuous  Terminal Location: Circumference  Voltage Rating In Volts: 15.0 dc  Mounting Facility Type And Quantity: 1 threaded hole  Storage Type: General purpose warehouse Thready Qty Per Inch (tpi): 56 mounting facility hole  Actuator Stroke Type: Rotary
Electrical Resistance: 300.00 ohms  Duty Type: Continuous  Terminal Location: Circumference Voltage Rating In Volts: 15.0 dc  Mounting Facility Type And Quantity: 1 threaded hole Storage Type: General purpose warehouse Thready Qty Per Inch (tpi): 56 mounting facility hole Actuator Stroke Type: Rotary Power Takeoff Connection Type:

## NSN 5945-01-190-6832

Electrical Solenoid - Page 2 of 2

**Fiig:** A134a0



Mounting Facility Pattern:
Single position
Rotation Direction And Energizing Stroke In Angular Deg:
35.0 counterclockwise
Thread Series Designator:
Unc mounting facility hole
Terminal Type And Quantity:
2 wire lead
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No