# NSN 5945-01-190-7323

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-190-7323

## **Overall Length:**

6.125 inches

## Center To Center Distance Between Mounting Facilities Parallel To Length:

3.750 inches single mounting facility

## Center To Center Distance Between Mounting Facilities Parallel To Width:

2.500 inches single mounting facility

### **Overall Height:**

4.750 inches

**Overall Width:** 

2.875 inches

Case Material:

Metal

**Environmental Protection:** 

Dustproof

**Unthreaded Mounting Hole Diameter:** 

0.219 inches single mounting facility

#### **Fragility Factor:**

Moderately rugged

Frequency In Hertz:

60.0

Winding Quantity:

1

Purpose For Which Designed:

General

#### **Coil Quantity:**

1

Duty Type:

Continuous

Arc Quenching Method:

Air

#### Mounting Facility Type And Quantity:

4 unthreaded hole single mounting facility

Storage Type:

General purpose warehouse

Cubic Measure:

83.644 cubic inches

Mounting Facility Pattern:

Rectangular single mounting facility

#### Nonpile-up Main Contact Arrangement:

2 pole, single throw, normally open, momentary action and 2 pole, single throw, normally closed, momentary action

Time Delay:

0.20 seconds fixed operate and release time

## NSN 5945-01-190-7323

Electromagnetic Relay - Page 2 of 2



Operating Voltage Rating And Type At Specificationified Temp:

110.0 volts ac 25 degrees celsius single winding

#### Main Contact Load Current Rating At Maximum Rated Voltage:

15.0 amperes ac resistive load

Main Contact Maximum Voltage Rating In Volts:

440.0 ac

Terminal Type And Quantity:

10 screw all functions

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A03300