## NSN 5945-01-190-7324

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-190-7324

| Overall Length:   |  |  |  |  |  |
|---|--|--|--|--|--|
| 4.375 inches  |  |  |  |  |  |
| Center To Center Distance Between Mounting Facilities Parallel To Length:   |  |  |  |  |  |
| 4.000 inches single mounting facility   |  |  |  |  |  |
| Overall Height:   |  |  |  |  |  |
| 4.562 inches  |  |  |  |  |  |
| Overall Width:  |  |  |  |  |  |
| 4.125 inches  |  |  |  |  |  |
| Case Material:  |  |  |  |  |  |
| Metal   |  |  |  |  |  |
| Environmental Protection:   |  |  |  |  |  |
| Dustproof   |  |  |  |  |  |
| Unthreaded Mounting Hole Diameter:  |  |  |  |  |  |
| 0.199 inches single mounting facility   |  |  |  |  |  |
| Fragility Factor:   |  |  |  |  |  |
| Moderately rugged   |  |  |  |  |  |
| Frequency In Hertz:   |  |  |  |  |  |
| 60.0  |  |  |  |  |  |
| Winding Quantity:   |  |  |  |  |  |
| 1   |  |  |  |  |  |
| Purpose For Which Designed:   |  |  |  |  |  |
| General   |  |  |  |  |  |
| Coil Quantity:  |  |  |  |  |  |
| 1   |  |  |  |  |  |
| Duty Type:  |  |  |  |  |  |
| Continuous  |  |  |  |  |  |
| Arc Quenching Method:   |  |  |  |  |  |
| Air   |  |  |  |  |  |
| Mounting Facility Type And Quantity:  |  |  |  |  |  |
| 2 unthreaded hole single mounting facility  |  |  |  |  |  |
| Storage Type:   |  |  |  |  |  |
| General purpose warehouse   |  |  |  |  |  |
| Cubic Measure:  |  |  |  |  |  |
| 82.329 cubic inches   |  |  |  |  |  |
| Mounting Facility Pattern:  |  |  |  |  |  |
| In-line single mounting facility  |  |  |  |  |  |
| Nonpile-up Main Contact Arrangement:  |  |  |  |  |  |
| 2 pole, single throw, normally open, momentary action and 2 pole, single throw, normally closed, momentary action |  |  |  |  |  |
| Operating Voltage Rating And Type At Specificationified Temp:   |  |  |  |  |  |
| 440.0 volts ac 25 degrees celsius single winding  |  |  |  |  |  |
| Main Contact Load Current Rating At Maximum Rated Voltage:  |  |  |  |  |  |

10.0 amperes ac resistive load

## NSN 5945-01-190-7324

Electromagnetic Relay - Page 2 of 2



| Main | Contact | Maximum | Voltage | Rating | In Volts: |
|------|---------|---------|---------|--------|-----------|
|------|---------|---------|---------|--------|-----------|

440.0 ac

**Terminal Type And Quantity:** 

10 screw all functions

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A03300