## NSN 5945-01-191-3194

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-191-3194

view Offilite at https://aerobasegroup.com/nsi//0940-01-191-0194
Overall Length:
6.594 inches
Center To Center Distance Between Mounting Facilities Parallel To Width:
5.516 inches single mounting facility
Overall Height:
10.047 inches
Overall Width:
6.125 inches
Mounting Slot Width:
0.201 inches single mounting facility
Case Material:
Plastic
Fragility Factor:
Moderately rugged
Frequency In Hertz:
60.0
Winding Quantity:
1
Purpose For Which Designed:
General
Coil Quantity:
1
Duty Type:
Continuous
Arc Quenching Method:
Air
Mounting Facility Type And Quantity:
3 slotted hole single mounting facility
Storage Type:
General purpose warehouse
Cubic Measure:
405.781 cubic inches
Mounting Facility Pattern:
Triangle single mounting facility
Nonpile-up Main Contact Arrangement:
3 pole, single throw, normally open, momentary action
Nonpile-up Auxiliary Contact Arrangement:
1 pole, single throw, normally open, momentary action
Auxiliary Contact Maximum Voltage Rating In Volts:
120.0 ac
Center To Center Distance Between Mounting Facilities Parallel To The Altitude Of An Isosceles Triangle:

8.656 inches single mounting facility

## NSN 5945-01-191-3194

Electromagnetic Relay - Page 2 of 2



## Operating Voltage Rating And Type At Specificationified Temp:

120.0 volts ac 25 degrees celsius single winding

Main Contact Load Current Rating At Maximum Rated Voltage:

90.0 amperes ac motor load

**Main Contact Maximum Voltage Rating In Volts:** 

240.0 ac

**Auxiliary Contact Load Current Rating At Maximum Rated Voltage:** 

10.0 probe ac motor load

**Terminal Type And Quantity:** 

10 screw all functions

Shelf Life:

N/a

**Unit Of Measure:** 

\_\_

**Demilitarization:** 

No

Fiig:

A03300