NSN 5945-01-191-3194

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-191-3194

Overall Length:	
6.594 inches	
Center To Center Dista	ance Between Mounting Facilities Parallel To Width:
5.516 inches single mo	unting facility
Overall Height:	
10.047 inches	
Overall Width:	
6.125 inches	
Mounting Slot Width:	
0.201 inches single more	unting facility
Case Material:	
Plastic	
Fragility Factor:	
Moderately rugged	
Frequency In Hertz:	
60.0	
Winding Quantity:	
1	
Purpose For Which De	signed:
General	
Coil Quantity:	
1	
Duty Type:	
Continuous	
Arc Quenching Method	d:
Air	
Mounting Facility Type	And Quantity:
3 slotted hole single more	unting facility
Storage Type:	
General purpose wareho	ouse
Cubic Measure:	
405.781 cubic inches	
Mounting Facility Patte	ern:
Triangle single mounting	j facility
Nonpile-up Main Conta	act Arrangement:
3 pole, single throw, no	prmally open, momentary action
Nonpile-up Auxiliary C	contact Arrangement:
1 pole, single throw, no	ormally open, momentary action
Auxiliary Contact Maxi	imum Voltage Rating In Volts:
120.0 ac	
Center To Center Dista	ance Between Mounting Facilities Parallel To The Altitude Of An Isosceles Triangle

8.656 inches single mounting facility

NSN 5945-01-191-3194

Electromagnetic Relay - Page 2 of 2



Operating Voltage Rating And Type At Specificationified Temp:

120.0 volts ac 25 degrees celsius single winding

Main Contact Load Current Rating At Maximum Rated Voltage:

90.0 amperes ac motor load

Main Contact Maximum Voltage Rating In Volts:

240.0 ac

Auxiliary Contact Load Current Rating At Maximum Rated Voltage:

10.0 probe ac motor load

Terminal Type And Quantity:

10 screw all functions

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A03300