NSN 5945-01-192-3202

Reed Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-192-3202

2.718 inches Overall Height: 0.656 inches Overall Width: 0.687 inches Case Material: Metal Environmental Protection: Dustproof Fragility Factor: Moderately rugged Winding Quantity: 1 Purpose For Which Designed: General Coil Quantity: 1 Winding Dc Resistance Rating: 1.6 kilohms single winding Duty Type: Continuous Mounting Facility Type And Quantity: 1 printed circuit terminal single mounting facility Storage Type: General purpose warehouse Features Provided: Magnetic shield Cubic Measure: 1.225 cubic inches Nonpile-up Main Contact Arrangement: 2 pole, single throw, normally open, momentary action Operating Current Rating And Type: 15.0 milliamperes dc single winding Operating Voltage Rating And Type At Specificationified Temp:	
Overall Width: 0.687 inches Case Material: Metal Environmental Protection: Dustproof Fragility Factor: Moderately rugged Winding Quantity: 1 Purpose For Which Designed: General Coil Quantity: 1 Winding Dc Resistance Rating: 1.6 kilohms single winding Duty Type: Continuous Mounting Facility Type And Quantity: 1 printed circuit terminal single mounting facility Storage Type: General purpose warehouse Features Provided: Magnetic shield Cubic Measure: 1.225 cubic inches Nonpile-up Main Contact Arrangement: 2 pole, single throw, normally open, momentary action Operating Current Rating And Type: 15.0 milliamperes dc single winding	
Overall Width: 0.687 inches Case Material: Metal Environmental Protection: Dustproof Fragility Factor: Moderately rugged Winding Quantity: 1 Purpose For Which Designed: General Coil Quantity: 1 Winding Dc Resistance Rating: 1.6 kilohms single winding Duty Type: Continuous Mounting Facility Type And Quantity: 1 printed circuit terminal single mounting facility Storage Type: General purpose warehouse Features Provided: Magnetic shield Cubic Measure: 1.225 cubic inches Nonpile-up Main Contact Arrangement: 2 pole, single throw, normally open, momentary action Operating Current Rating And Type: 15.0 milliamperes dc single winding	
Case Material: Metal Environmental Protection: Dustproof Fragility Factor: Moderately rugged Winding Quantity: 1 Purpose For Which Designed: General Coil Quantity: 1 Winding Dc Resistance Rating: 1.6 kilohms single winding Duty Type: Continuous Mounting Facility Type And Quantity: 1 printed circuit terminal single mounting facility Storage Type: General purpose warehouse Features Provided: Magnetic shield Cubic Measure: 1.225 cubic inches Nonpile-up Main Contact Arrangement: 2 pole, single throw, normally open, momentary action Operating Current Rating And Type: 15.0 milliamperes dc single winding	
Case Material: Metal Environmental Protection: Dustproof Fragility Factor: Moderately rugged Winding Quantity: 1 Purpose For Which Designed: General Coil Quantity: 1 Winding Dc Resistance Rating: 1.6 kilohms single winding Duty Type: Continuous Mounting Facility Type And Quantity: 1 printed circuit terminal single mounting facility Storage Type: General purpose warehouse Features Provided: Magnetic shield Cubic Measure: 1.225 cubic inches Nonpile-up Main Contact Arrangement: 2 pole, single throw, normally open, momentary action Operating Current Rating And Type: 15.0 milliamperes dc single winding	
Metal Environmental Protection: Dustproof Fragility Factor: Moderately rugged Winding Quantity: 1 Purpose For Which Designed: General Coil Quantity: 1 Winding Dc Resistance Rating: 1.6 kilohms single winding Duty Type: Continuous Mounting Facility Type And Quantity: 1 printed circuit terminal single mounting facility Storage Type: General purpose warehouse Features Provided: Magnetic shield Cubic Measure: 1.225 cubic inches Nonpile-up Main Contact Arrangement: 2 pole, single throw, normally open, momentary action Operating Current Rating And Type: 15.0 milliamperes dc single winding	
Environmental Protection: Dustproof Fragility Factor: Moderately rugged Winding Quantity: 1 Purpose For Which Designed: General Coil Quantity: 1 Winding Dc Resistance Rating: 1.6 kilohms single winding Duty Type: Continuous Mounting Facility Type And Quantity: 1 printed circuit terminal single mounting facility Storage Type: General purpose warehouse Features Provided: Magnetic shield Cubic Measure: 1.225 cubic inches Nonpile-up Main Contact Arrangement: 2 pole, single throw, normally open, momentary action Operating Current Rating And Type: 15.0 milliamperes dc single winding	
Dustproof Fragility Factor: Moderately rugged Winding Quantity: 1 Purpose For Which Designed: General Coil Quantity: 1 Winding Dc Resistance Rating: 1.6 kilohms single winding Duty Type: Continuous Mounting Facility Type And Quantity: 1 printed circuit terminal single mounting facility Storage Type: General purpose warehouse Features Provided: Magnetic shield Cubic Measure: 1.225 cubic inches Nonpile-up Main Contact Arrangement: 2 pole, single throw, normally open, momentary action Operating Current Rating And Type: 15.0 milliamperes dc single winding	
Fragility Factor: Moderately rugged Winding Quantity: 1 Purpose For Which Designed: General Coil Quantity: 1 Winding Dc Resistance Rating: 1.6 kilohms single winding Duty Type: Continuous Mounting Facility Type And Quantity: 1 printed circuit terminal single mounting facility Storage Type: General purpose warehouse Features Provided: Magnetic shield Cubic Measure: 1.225 cubic inches Nonpile-up Main Contact Arrangement: 2 pole, single throw, normally open, momentary action Operating Current Rating And Type: 15.0 milliamperes dc single winding	
Moderately rugged Winding Quantity: 1 Purpose For Which Designed: General Coil Quantity: 1 Winding Dc Resistance Rating: 1.6 kilohms single winding Duty Type: Continuous Mounting Facility Type And Quantity: 1 printed circuit terminal single mounting facility Storage Type: General purpose warehouse Features Provided: Magnetic shield Cubic Measure: 1.225 cubic inches Nonpile-up Main Contact Arrangement: 2 pole, single throw, normally open, momentary action Operating Current Rating And Type: 15.0 milliamperes dc single winding	
Winding Quantity: Purpose For Which Designed: General Coil Quantity: Winding Dc Resistance Rating: 1.6 kilohms single winding Duty Type: Continuous Mounting Facility Type And Quantity: 1 printed circuit terminal single mounting facility Storage Type: General purpose warehouse Features Provided: Magnetic shield Cubic Measure: 1.225 cubic inches Nonpile-up Main Contact Arrangement: 2 pole, single throw, normally open, momentary action Operating Current Rating And Type: 15.0 milliamperes dc single winding	
Purpose For Which Designed: General Coil Quantity: 1 Winding Dc Resistance Rating: 1.6 kilohms single winding Duty Type: Continuous Mounting Facility Type And Quantity: 1 printed circuit terminal single mounting facility Storage Type: General purpose warehouse Features Provided: Magnetic shield Cubic Measure: 1.225 cubic inches Nonpile-up Main Contact Arrangement: 2 pole, single throw, normally open, momentary action Operating Current Rating And Type: 15.0 milliamperes dc single winding	
Purpose For Which Designed: General Coil Quantity: 1 Winding Dc Resistance Rating: 1.6 kilohms single winding Duty Type: Continuous Mounting Facility Type And Quantity: 1 printed circuit terminal single mounting facility Storage Type: General purpose warehouse Features Provided: Magnetic shield Cubic Measure: 1.225 cubic inches Nonpile-up Main Contact Arrangement: 2 pole, single throw, normally open, momentary action Operating Current Rating And Type: 15.0 milliamperes dc single winding	
Coil Quantity: 1 Winding Dc Resistance Rating: 1.6 kilohms single winding Duty Type: Continuous Mounting Facility Type And Quantity: 1 printed circuit terminal single mounting facility Storage Type: General purpose warehouse Features Provided: Magnetic shield Cubic Measure: 1.225 cubic inches Nonpile-up Main Contact Arrangement: 2 pole, single throw, normally open, momentary action Operating Current Rating And Type: 15.0 milliamperes dc single winding	
Coil Quantity: Winding Dc Resistance Rating: 1.6 kilohms single winding Duty Type: Continuous Mounting Facility Type And Quantity: 1 printed circuit terminal single mounting facility Storage Type: General purpose warehouse Features Provided: Magnetic shield Cubic Measure: 1.225 cubic inches Nonpile-up Main Contact Arrangement: 2 pole, single throw, normally open, momentary action Operating Current Rating And Type: 15.0 milliamperes dc single winding	
Winding Dc Resistance Rating: 1.6 kilohms single winding Duty Type: Continuous Mounting Facility Type And Quantity: 1 printed circuit terminal single mounting facility Storage Type: General purpose warehouse Features Provided: Magnetic shield Cubic Measure: 1.225 cubic inches Nonpile-up Main Contact Arrangement: 2 pole, single throw, normally open, momentary action Operating Current Rating And Type: 15.0 milliamperes dc single winding	
Winding Dc Resistance Rating: 1.6 kilohms single winding Duty Type: Continuous Mounting Facility Type And Quantity: 1 printed circuit terminal single mounting facility Storage Type: General purpose warehouse Features Provided: Magnetic shield Cubic Measure: 1.225 cubic inches Nonpile-up Main Contact Arrangement: 2 pole, single throw, normally open, momentary action Operating Current Rating And Type: 15.0 milliamperes dc single winding	
1.6 kilohms single winding Duty Type: Continuous Mounting Facility Type And Quantity: 1 printed circuit terminal single mounting facility Storage Type: General purpose warehouse Features Provided: Magnetic shield Cubic Measure: 1.225 cubic inches Nonpile-up Main Contact Arrangement: 2 pole, single throw, normally open, momentary action Operating Current Rating And Type: 15.0 milliamperes dc single winding	
Duty Type: Continuous Mounting Facility Type And Quantity: 1 printed circuit terminal single mounting facility Storage Type: General purpose warehouse Features Provided: Magnetic shield Cubic Measure: 1.225 cubic inches Nonpile-up Main Contact Arrangement: 2 pole, single throw, normally open, momentary action Operating Current Rating And Type: 15.0 milliamperes dc single winding	
Continuous Mounting Facility Type And Quantity: 1 printed circuit terminal single mounting facility Storage Type: General purpose warehouse Features Provided: Magnetic shield Cubic Measure: 1.225 cubic inches Nonpile-up Main Contact Arrangement: 2 pole, single throw, normally open, momentary action Operating Current Rating And Type: 15.0 milliamperes dc single winding	
Mounting Facility Type And Quantity: 1 printed circuit terminal single mounting facility Storage Type: General purpose warehouse Features Provided: Magnetic shield Cubic Measure: 1.225 cubic inches Nonpile-up Main Contact Arrangement: 2 pole, single throw, normally open, momentary action Operating Current Rating And Type: 15.0 milliamperes dc single winding	
1 printed circuit terminal single mounting facility Storage Type: General purpose warehouse Features Provided: Magnetic shield Cubic Measure: 1.225 cubic inches Nonpile-up Main Contact Arrangement: 2 pole, single throw, normally open, momentary action Operating Current Rating And Type: 15.0 milliamperes dc single winding	
Storage Type: General purpose warehouse Features Provided: Magnetic shield Cubic Measure: 1.225 cubic inches Nonpile-up Main Contact Arrangement: 2 pole, single throw, normally open, momentary action Operating Current Rating And Type: 15.0 milliamperes dc single winding	
General purpose warehouse Features Provided: Magnetic shield Cubic Measure: 1.225 cubic inches Nonpile-up Main Contact Arrangement: 2 pole, single throw, normally open, momentary action Operating Current Rating And Type: 15.0 milliamperes dc single winding	
Features Provided: Magnetic shield Cubic Measure: 1.225 cubic inches Nonpile-up Main Contact Arrangement: 2 pole, single throw, normally open, momentary action Operating Current Rating And Type: 15.0 milliamperes dc single winding	
Magnetic shield Cubic Measure: 1.225 cubic inches Nonpile-up Main Contact Arrangement: 2 pole, single throw, normally open, momentary action Operating Current Rating And Type: 15.0 milliamperes dc single winding	
Cubic Measure: 1.225 cubic inches Nonpile-up Main Contact Arrangement: 2 pole, single throw, normally open, momentary action Operating Current Rating And Type: 15.0 milliamperes dc single winding	
1.225 cubic inches Nonpile-up Main Contact Arrangement: 2 pole, single throw, normally open, momentary action Operating Current Rating And Type: 15.0 milliamperes dc single winding	
Nonpile-up Main Contact Arrangement: 2 pole, single throw, normally open, momentary action Operating Current Rating And Type: 15.0 milliamperes dc single winding	
2 pole, single throw, normally open, momentary actionOperating Current Rating And Type:15.0 milliamperes dc single winding	
Operating Current Rating And Type: 15.0 milliamperes dc single winding	
15.0 milliamperes dc single winding	
Operating Voltage Rating And Type At Specificationified Temp:	
24.0 volts dc 25 degrees celsius single winding	
Main Contact Load Current Rating At Maximum Rated Voltage:	
1.0 amperes dc resistive load	
Main Contact Maximum Voltage Rating In Volts:	
250.0 dc	

360.0 milliwatts

NSN 5945-01-192-3202

Reed Relay - Page 2 of 2



Terminal Type Ar	nd Quantity:
------------------	--------------

1 printed circuit all functions

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A03300