NSN 5945-01-192-7248

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-192-7248
Overall Length:
1.718 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
1.396 inches single mounting facility and 1.446 inches single mounting facility
Center To Center Distance Between Mounting Facilities Parallel To Width:
0.625 inches single mounting facility
Overall Height:
1.352 inches
Overall Width:
1.025 inches
Mounting Slot Width:
0.150 inches single mounting facility
Case Material:
Metal
Environmental Protection:
Hermetic and shock resistant and vibration resistant
Fragility Factor:
Moderately rugged
Frequency In Hertz:
400.0
Winding Quantity:
1
Purpose For Which Designed:
General
Coil Quantity:
1
Duty Type:
Continuous
Arc Quenching Method:
Air
Mounting Facility Type And Quantity:
4 slotted hole single mounting facility
Storage Type:
General purpose warehouse
Cubic Measure:
2.381 cubic inches
Mounting Facility Pattern:
Rectangular single mounting facility
Nonpile-up Main Contact Arrangement:

Operating Current Rating And Type:

3 pole, single throw, normally open, momentary action

25.0 milliamperes ac single winding

NSN 5945-01-192-7248

Electromagnetic Relay - Page 2 of 2



Time D	elay:
--------	-------

0.04 seconds fixed release time

Nonpile-up Auxiliary Contact Arrangement:

1 pole, double throw, one position momentary

Operating Voltage Rating And Type At Specificationified Temp:

230.0 volts ac 25 degrees celsius single winding

Main Contact Load Current Rating At Maximum Rated Voltage:

2.5 amperes ac lamp load and 2.5 amperes dc lamp load

Main Contact Maximum Voltage Rating In Volts:

230.0 ac and 28.0 dc

Auxiliary Contact Load Current Rating At Maximum Rated Voltage:

500.0 milliamperes ac lamp load and 500.0 milliamperes dc lamp load

Precious Material And Location:

Terminal surfaces gold

Precious Material:

Gold

Terminal Type And Quantity:

11 pin all functions

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A03300