

View Online at <https://aerobasegroup.com/nsn/5945-01-192-7988>

**Overall Length:**

2.940 inches

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

2.500 inches single mounting facility

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

1.063 inches single mounting facility

**Overall Height:**

2.790 inches

**Overall Width:**

1.900 inches

**Case Material:**

Metal

**Environmental Protection:**

Hermetic

**Unthreaded Mounting Hole Diameter:**

0.193 inches single mounting facility

**Fragility Factor:**

Moderately rugged

**Winding Quantity:**

1

**Purpose For Which Designed:**

General

**Coil Quantity:**

1

**Duty Type:**

Continuous

**Arc Quenching Method:**

Air

**Mounting Facility Type And Quantity:**

4 unthreaded hole single mounting facility

**Storage Type:**

General purpose warehouse

**Features Provided:**

Polarized

**Cubic Measure:**

15.585 cubic inches

**Mounting Facility Pattern:**

Rectangular single mounting facility

**Nonpile-up Main Contact Arrangement:**

3 pole, double throw, double break/double make, permanent jumper, one position momentary

**Operating Current Rating And Type:**

170.0 milliamperes dc single winding

**Time Delay:**

0.025 seconds fixed operate and release time

**Nonpile-up Auxiliary Contact Arrangement:**

1 pole, single throw, normally open, momentary action and 1 pole, single throw, normally closed, momentary action

**Auxiliary Contact Maximum Voltage Rating In Volts:**

28.0 dc

**Operating Voltage Rating And Type At Specificationified Temp:**

28.0 volts dc 25 degrees celsius single winding

**Main Contact Load Current Rating At Maximum Rated Voltage:**

10.0 amperes ac motor load

**Main Contact Maximum Voltage Rating In Volts:**

115.0 ac

**Auxiliary Contact Load Current Rating At Maximum Rated Voltage:**

500.0 milliamperes dc lamp load

**Terminal Type And Quantity:**

15 threaded stud all functions

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A03300