# NSN 5945-01-192-7992

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-192-7992

# Overall Length:

3.320 inches

# Center To Center Distance Between Mounting Facilities Parallel To Width:

2.880 inches single mounting facility

# **Overall Height:**

5.820 inches

# **Overall Width:**

3.250 inches

**Case Material:** 

Plastic

#### **Unthreaded Mounting Hole Diameter:**

0.199 inches single mounting facility

# Center To Center Distance Between Mounting Facilities Parallel To Height:

0.750 inches single mounting facility

#### **Fragility Factor:**

# Moderately rugged

Frequency In Hertz:

#### 60.0

Winding Quantity:

1

**Purpose For Which Designed:** 

General

#### **Coil Quantity:**

1

# Duty Type:

Continuous

# Arc Quenching Method:

Air

#### Mounting Facility Type And Quantity:

6 unthreaded hole single mounting facility

#### Storage Type:

General purpose warehouse

#### **Cubic Measure:**

62.978 cubic inches

#### **Mounting Facility Pattern:**

Rectangular single mounting facility

### Nonpile-up Main Contact Arrangement:

4 pole, double throw, one position momentary

#### Time Delay:

20.00 seconds adjustable release time and 200.00 seconds adjustable release time

# Operating Voltage Rating And Type At Specificationified Temp:

110.0 volts ac 25 degrees celsius single winding

# NSN 5945-01-192-7992

Electromagnetic Relay - Page 2 of 2



# Main Contact Load Current Rating At Maximum Rated Voltage:

10.0 amperes ac resistive load and 500.0 milliamperes dc resistive load

#### Main Contact Maximum Voltage Rating In Volts:

480.0 ac and 110.0 dc

# Terminal Type And Quantity:

14 screw all functions

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A03300