# NSN 5945-01-193-0234

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-193-0234

### **Overall Length:**

3.733 inches

### Center To Center Distance Between Mounting Facilities Parallel To Length:

3.250 inches single mounting facility

## Center To Center Distance Between Mounting Facilities Parallel To Width:

2.687 inches single mounting facility

#### **Overall Height:**

2.438 inches

**Overall Width:** 

3.300 inches

**Environmental Protection:** 

Hermetic

**Unthreaded Mounting Hole Diameter:** 

0.218 inches single mounting facility

### Winding Quantity:

1

Coil Quantity:

1

Winding Dc Resistance Rating:

50.0 ohms single winding

Duty Type:

Continuous

Mounting Facility Type And Quantity:

4 unthreaded hole single mounting facility

#### Mounting Facility Pattern:

Rectangular single mounting facility

### Nonpile-up Main Contact Arrangement:

3 pole, single throw, normally open, double make, momentary action

### **Operating Current Rating And Type:**

640.0 milliamperes dc single winding

#### Time Delay:

0.025 seconds fixed operate time

### Nonpile-up Auxiliary Contact Arrangement:

1 two circuit, double break/double make, one position momentary

### **Operating Voltage Rating And Type At Specificationified Temp:**

28.0 volts dc 25 degrees celsius single winding

# Main Contact Load Current Rating At Maximum Rated Voltage:

50.0 amperes ac resistive load and 50.0 amperes dc resistive load

## Main Contact Maximum Voltage Rating In Volts:

200.0 ac and 28.0 dc

#### **Terminal Type And Quantity:**

12 threaded stud all functions

# NSN 5945-01-193-0234

Electromagnetic Relay - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A03300

