# NSN 5945-01-193-0235

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-193-0235

**Overall Length:** 

1.540 inches

**Overall Height:** 

0.570 inches

**Overall Width:** 

1.480 inches

**Case Material:** 

Plastic

Environmental Protection:

Dustproof

**Fragility Factor:** 

Moderately rugged

**Contact Material:** 

Silver

Contact Surface Treatment:

Gold flash

Winding Quantity:

1

**Purpose For Which Designed:** 

General

**Coil Quantity:** 

1

Winding Dc Resistance Rating:

769.0 ohms single winding

**Duty Type:** 

Continuous

Arc Quenching Method:

Air

Mounting Facility Type And Quantity:

1 printed circuit terminal single mounting facility

#### Storage Type:

General purpose warehouse

**Cubic Measure:** 

1.299 cubic inches

Nonpile-up Main Contact Arrangement:

4 pole, double throw, one position momentary

# Operating Current Rating And Type:

26.0 milliamperes dc single winding

Time Delay:

0.015 seconds fixed operate and release time

# Operating Voltage Rating And Type At Specificationified Temp:

24.0 volts dc 25 degrees celsius single winding

# NSN 5945-01-193-0235

Electromagnetic Relay - Page 2 of 2



# Main Contact Load Current Rating At Maximum Rated Voltage:

1.0 amperes ac resistive load and 1.0 amperes dc resistive load

#### Main Contact Maximum Voltage Rating In Volts:

120.0 ac and 60.0 dc

# **Energizing Element Power Rating:**

800.0 milliwatts

### **Precious Material And Location:**

Contacts silver and contact surfaces gold

#### **Precious Material:**

Gold and silver

### Terminal Type And Quantity:

1 printed circuit all functions

Shelf Life:

N/a

#### Unit Of Measure:

---

#### Demilitarization:

Yes - demil/mli

## Fiig:

A03300