NSN 5945-01-193-1364

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-193-1364

view Online at https://aerobasegroup.com/hsn/o945-01-195-1364
Overall Length:
1.718 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
1.406 inches single mounting facility
Center To Center Distance Between Mounting Facilities Parallel To Width:
0.500 inches single mounting facility
Overall Height:
1.480 inches
Overall Width:
0.852 inches
Mounting Slot Width:
0.150 inches single mounting facility
Case Material:
Metal
Environmental Protection:
Hermetic
Fragility Factor:
Moderately rugged
Contact Material:
Silver
Contact Surface Treatment:
Gold
Winding Quantity:
1
Purpose For Which Designed:
General
Coil Quantity:
1
Winding Dc Resistance Rating:
1.0 kilohms single winding
Duty Type:
Continuous
Arc Quenching Method:
Air
Mounting Facility Type And Quantity:
4 slotted hole single mounting facility
Storage Type:
General purpose warehouse

0.105 cubic inches

Mounting Facility Pattern:

Rectangular single mounting facility

NSN 5945-01-193-1364

Electromagnetic Relay - Page 2 of 2



Nonpile-up Main Contact Arrangement:

6 pole, double throw, one position momentary

Operating Current Rating And Type:

18.4 milliamperes dc single winding

Time Delay:

0.018 seconds fixed operate time

Operating Voltage Rating And Type At Specificationified Temp:

26.5 volts dc 25 degrees celsius single winding

Main Contact Load Current Rating At Maximum Rated Voltage:

2.0 amperes ac resistive load and 3.0 amperes dc resistive load

Main Contact Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Precious Material And Location:

Contacts silver and contact surfaces gold

Precious Material:

Gold and silver

Terminal Type And Quantity:

20 wire hook all functions

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A03300