

View Online at <https://aerobasegroup.com/nsn/5945-01-193-4949>

Overall Length:

3.430 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.750 inches single mounting facility

Center To Center Distance Between Mounting Facilities Parallel To Width:

3.062 inches single mounting facility

Overall Height:

3.720 inches

Overall Width:

3.750 inches

Case Material:

Metal

Environmental Protection:

Shock resistant and vibration resistant

Unthreaded Mounting Hole Diameter:

0.191 inches single mounting facility and 0.206 inches single mounting facility

Fragility Factor:

Moderately rugged

Contact Material:

Steel, corrosion resisting

Frequency In Hertz:

400.0

Winding Quantity:

1

Purpose For Which Designed:

General

Coil Quantity:

1

Winding Dc Resistance Rating:

113.0 ohms single winding

Duty Type:

Continuous

Arc Quenching Method:

Air

Mounting Facility Type And Quantity:

4 unthreaded hole single mounting facility

Storage Type:

General purpose warehouse

Features Provided:

Polarized

Cubic Measure:

47.848 cubic inches

Mounting Facility Pattern:

Rectangular single mounting facility

Nonpile-up Main Contact Arrangement:

3 pole, single throw, normally open, momentary action

Auxiliary Contact Maximum Voltage Rating In Volts:

28.0 dc

Operating Voltage Rating And Type At Specificationified Temp:

28.0 volts dc 25 degrees celsius all windings

Main Contact Load Current Rating At Maximum Rated Voltage:

120.0 amperes ac resistive load

Main Contact Maximum Voltage Rating In Volts:

200.0 ac

Auxiliary Contact Load Current Rating At Maximum Rated Voltage:

5.0 amperes dc resistive load

Special Features:

Auxiliary contact configuration; one spst nc and one spdt

Terminal Type And Quantity:

11 threaded stud all functions

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A03300