

View Online at <https://aerobasegroup.com/nsn/5945-01-193-4949>

**Overall Length:**

3.430 inches

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

2.750 inches single mounting facility

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

3.062 inches single mounting facility

**Overall Height:**

3.720 inches

**Overall Width:**

3.750 inches

**Case Material:**

Metal

**Environmental Protection:**

Shock resistant and vibration resistant

**Unthreaded Mounting Hole Diameter:**

0.191 inches single mounting facility and 0.206 inches single mounting facility

**Fragility Factor:**

Moderately rugged

**Contact Material:**

Steel, corrosion resisting

**Frequency In Hertz:**

400.0

**Winding Quantity:**

1

**Purpose For Which Designed:**

General

**Coil Quantity:**

1

**Winding Dc Resistance Rating:**

113.0 ohms single winding

**Duty Type:**

Continuous

**Arc Quenching Method:**

Air

**Mounting Facility Type And Quantity:**

4 unthreaded hole single mounting facility

**Storage Type:**

General purpose warehouse

**Features Provided:**

Polarized

**Cubic Measure:**

47.848 cubic inches

**Mounting Facility Pattern:**

Rectangular single mounting facility

**Nonpile-up Main Contact Arrangement:**

3 pole, single throw, normally open, momentary action

**Auxiliary Contact Maximum Voltage Rating In Volts:**

28.0 dc

**Operating Voltage Rating And Type At Specificationified Temp:**

28.0 volts dc 25 degrees celsius all windings

**Main Contact Load Current Rating At Maximum Rated Voltage:**

120.0 amperes ac resistive load

**Main Contact Maximum Voltage Rating In Volts:**

200.0 ac

**Auxiliary Contact Load Current Rating At Maximum Rated Voltage:**

5.0 amperes dc resistive load

**Special Features:**

Auxiliary contact configuration; one spst nc and one spdt

**Terminal Type And Quantity:**

11 threaded stud all functions

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A03300