NSN 5945-01-194-7537

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-194-7537

| Overall Length: |
|---|
| 0.370 inches |
| Overall Height: |
| 0.375 inches |
| Overall Width: |
| 0.370 inches |
| Case Material: |
| Metal |
| Environmental Protection: |
| Hermetic |
| Fragility Factor: |
| Moderately rugged |
| Contact Material: |
| Platinum |
| Contact Surface Treatment: |
| Gold |
| Winding Quantity: |
| 1 |
| Purpose For Which Designed: |
| General |
| Coil Quantity: |
| 1 |
| Winding Dc Resistance Rating: |
| 3.2 kilohms single winding |
| Duty Type: |
| Continuous |
| Arc Quenching Method: |
| Air |
| Mounting Facility Type And Quantity: |
| 1 terminal single mounting facility |
| Storage Type: |
| General purpose warehouse |
| Features Provided: |
| Coil voltage suppression and polarized |
| Cubic Measure: |
| 0.051 cubic inches |
| Nonpile-up Main Contact Arrangement: |
| 2 pole, double throw, one position momentary |
| Time Delay: |
| 0.0075 seconds fixed release time |
| Operating Voltage Rating And Type At Specificationified Temp: |
| 26.0 volts dc 25 degrees celsius single winding |

NSN 5945-01-194-7537

Electromagnetic Relay - Page 2 of 2



Main Contact Load Current Rating At Maximum Rated Voltage:

600.0 milliamperes ac resistive load and 1.0 amperes dc resistive load

Main Contact Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Special Features:

Supplied with mounting pad

Precious Material And Location:

Contacts platinum and contact surfaces gold

Precious Material:

Platinum and gold

Terminal Type And Quantity:

8 wire lead all functions

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A03300