NSN 5945-01-194-7540

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-194-7540

Overall Length:
3.090 inches
Center To Center Distance Between Mounting Facilities Parallel To Width:
2.880 inches single mounting facility
Overall Height:
6.230 inches
Overall Width:
3.250 inches
Case Material:
Plastic
Unthreaded Mounting Hole Diameter:
0.199 inches single mounting facility
Center To Center Distance Between Mounting Facilities Parallel To Height:
0.750 inches single mounting facility
Winding Quantity:
1
Purpose For Which Designed:
General
Coil Quantity:
1
Duty Type:
Continuous
Arc Quenching Method:
Air
Mounting Facility Type And Quantity:
6 unthreaded hole single mounting facility
Storage Type:
General purpose warehouse
Cubic Measure:
62.565 cubic inches
Mounting Facility Pattern:
Rectangular single mounting facility
Nonpile-up Main Contact Arrangement:
2 pole, double throw, one position momentary
Time Delay:
0.10 seconds adjustable operate time and 1.00 seconds adjustable operate time
Nonpile-up Auxiliary Contact Arrangement:
2 pole, double throw, one position momentary
Auxiliary Contact Maximum Voltage Rating In Volts:
490.0 ag and 110.0 da

110.0 volts ac 25 degrees celsius single winding

Operating Voltage Rating And Type At Specificationified Temp:

NSN 5945-01-194-7540

Electromagnetic Relay - Page 2 of 2



Main Contact Load Current Rating At Maximum Rated Voltage:

10.0 amperes ac resistive load and 500.0 milliamperes dc resistive load

Main Contact Maximum Voltage Rating In Volts:

480.0 ac and 110.0 dc

Auxiliary Contact Load Current Rating At Maximum Rated Voltage:

10.0 probe ac resistive load and 500.0 dual 16 stage dc resistive load

Special Features:

Auxiliary switch with two instantaneous form c contacts

Terminal Type And Quantity:

14 screw all functions

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A03300