

View Online at <https://aerobasegroup.com/nsn/5945-01-194-7540>

Overall Length:

3.090 inches

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.880 inches single mounting facility

Overall Height:

6.230 inches

Overall Width:

3.250 inches

Case Material:

Plastic

Unthreaded Mounting Hole Diameter:

0.199 inches single mounting facility

Center To Center Distance Between Mounting Facilities Parallel To Height:

0.750 inches single mounting facility

Winding Quantity:

1

Purpose For Which Designed:

General

Coil Quantity:

1

Duty Type:

Continuous

Arc Quenching Method:

Air

Mounting Facility Type And Quantity:

6 unthreaded hole single mounting facility

Storage Type:

General purpose warehouse

Cubic Measure:

62.565 cubic inches

Mounting Facility Pattern:

Rectangular single mounting facility

Nonpile-up Main Contact Arrangement:

2 pole, double throw, one position momentary

Time Delay:

0.10 seconds adjustable operate time and 1.00 seconds adjustable operate time

Nonpile-up Auxiliary Contact Arrangement:

2 pole, double throw, one position momentary

Auxiliary Contact Maximum Voltage Rating In Volts:

480.0 ac and 110.0 dc

Operating Voltage Rating And Type At Specificationified Temp:

110.0 volts ac 25 degrees celsius single winding

Main Contact Load Current Rating At Maximum Rated Voltage:

10.0 amperes ac resistive load and 500.0 milliamperes dc resistive load

Main Contact Maximum Voltage Rating In Volts:

480.0 ac and 110.0 dc

Auxiliary Contact Load Current Rating At Maximum Rated Voltage:

10.0 probe ac resistive load and 500.0 dual 16 stage dc resistive load

Special Features:

Auxiliary switch with two instantaneous form c contacts

Terminal Type And Quantity:

14 screw all functions

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A03300