# NSN 5945-01-195-7263

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-195-7263

#### **Overall Length:**

0.610 inches

**Overall Height:** 

0.450 inches

## **Overall Width:**

0.570 inches

#### **Case Material:**

Plastic

#### **Environmental Protection:**

Dustproof

**Fragility Factor:** 

## Moderately rugged

**Contact Material:** 

Gold

#### Winding Quantity:

1

#### Purpose For Which Designed:

General

## **Coil Quantity:**

1

## Winding Dc Resistance Rating:

1.15 kilohms single winding

#### Duty Type:

Continuous

#### Arc Quenching Method:

Air

## Mounting Facility Type And Quantity:

1 printed circuit terminal single mounting facility

#### Storage Type:

General purpose warehouse

#### **Features Provided:**

Electrostatic shield and polarized

#### **Cubic Measure:**

0.156 cubic inches

#### Nonpile-up Main Contact Arrangement:

1 pole, single throw, normally open, momentary action and 1 pole, single throw, normally closed, momentary action

#### **Operating Current Rating And Type:**

10.4 milliamperes dc single winding

#### Time Delay:

0.007 seconds fixed operate time

#### **Operating Voltage Rating And Type At Specificationified Temp:**

12.0 volts dc 25 degrees celsius single winding

# NSN 5945-01-195-7263

Electromagnetic Relay - Page 2 of 2



## Main Contact Load Current Rating At Maximum Rated Voltage:

300.0 milliamperes dc resistive load

#### Main Contact Maximum Voltage Rating In Volts:

30.0 dc

## **Energizing Element Power Rating:**

125.0 milliwatts

## Precious Material And Location:

Contacts gold

## **Precious Material:**

Gold

#### **Terminal Type And Quantity:**

1 printed circuit all functions

Shelf Life:

N/a

#### Unit Of Measure:

---

## Demilitarization:

No

## Fiig:

A03300