NSN 5945-01-196-5666

Electromagnetic Relay - Page 1 of 2



| view Online at https://aerobasegroup.com/hsn/5945-01-196-5666 |
|--|
| Overall Length: |
| 3.938 inches |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 2.000 inches single mounting facility |
| Overall Height: |
| 4.000 inches |
| Overall Width: |
| 3.500 inches |
| Environmental Protection: |
| Dustproof |
| Unthreaded Mounting Hole Diameter: |
| 0.201 inches single mounting facility |
| Fragility Factor: |
| Moderately rugged |
| Frequency In Hertz: |
| 60.0 |
| Winding Quantity: |
| 1 |
| Purpose For Which Designed: |
| General |
| Coil Quantity: |
| 1 |
| Duty Type: |
| Continuous |
| Arc Quenching Method: |
| Air |
| Mounting Facility Type And Quantity: |
| 3 unthreaded hole single mounting facility |
| Storage Type: |
| General purpose warehouse |
| Cubic Measure: |
| 55.132 cubic inches |
| Mounting Facility Pattern: |
| Triangle single mounting facility |
| Nonpile-up Main Contact Arrangement: |
| 4 pole, single throw, normally open, momentary action |
| Center To Center Distance Between Mounting Facilities Parallel To The Altitude Of An Isosceles Triangle: |
| 3.625 inches single mounting facility |
| Operating Voltage Rating And Type At Specificationified Temp: |
| 120.0 volts ac 25 degrees celsius single winding |

40.0 amperes ac resistive load

Main Contact Load Current Rating At Maximum Rated Voltage:

NSN 5945-01-196-5666

Electromagnetic Relay - Page 2 of 2



| Main Contact Maximum | Voltage | Rating | In ' | Volts: |
|----------------------|---------|--------|------|--------|
| | | | | |

230.0 ac

Terminal Type And Quantity:

10 screw all functions

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A03300