NSN 5945-01-198-6229

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-198-6229

Overall Length:

1.730 inches

Center To Center Distance Between Mounting Facilities Parallel To Width:

0.625 inches single mounting facility

Overall Height:

2.070 inches

Overall Width:

1.280 inches

Mounting Slot Width:

0.150 inches single mounting facility

Case Material:

Metal

Environmental Protection:

Hermetic

Fragility Factor:

Moderately rugged

Frequency In Hertz:

60.0

Winding Quantity:

1

Purpose For Which Designed:

General

Coil Quantity:

1

Duty Type:

Continuous

Arc Quenching Method:

Air

Mounting Facility Type And Quantity:

3 slotted hole single mounting facility

Storage Type:

General purpose warehouse

Cubic Measure:

4.584 cubic inches

Mounting Facility Pattern:

Triangle single mounting facility

Nonpile-up Main Contact Arrangement:

2 pole, double throw, one position momentary

Operating Current Rating And Type:

40.0 milliamperes ac single winding

Time Delay:

210.00 seconds fixed operate time

NSN 5945-01-198-6229

Electromagnetic Relay - Page 2 of 2



Center To Center Distance Between Mounting Facilities Parallel To The Altitude Of An Isosceles Triangle: 1.396 inches single mounting facility and 1.446 inches single mounting facility **Operating Voltage Rating And Type At Specificationified Temp:** 126.0 volts ac 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage: 2.0 amperes ac lamp load and 2.0 amperes dc lamp load Main Contact Maximum Voltage Rating In Volts: 115.0 ac and 28.0 dc **Precious Material And Location:** Terminal surfaces gold **Precious Material:** Gold **Terminal Type And Quantity:** 8 pin energizing element and contacts Shelf Life: N/a Unit Of Measure: ---**Demilitarization:** No Fiig: A03300