NSN 5945-01-199-5567

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-199-5567

| Overall Length: |
|---|
| 0.790 inches |
| Overall Height: |
| 1.080 inches |
| Overall Width: |
| 0.360 inches |
| Case Material: |
| Metal |
| Environmental Protection: |
| Dustproof |
| Fragility Factor: |
| Moderately rugged |
| Winding Quantity: |
| 1 |
| Purpose For Which Designed: |
| General |
| Coil Quantity: |
| 1 |
| Winding Dc Resistance Rating: |
| 540.0 ohms single winding and 660.0 ohms single winding |
| Duty Type: |
| Continuous |
| Arc Quenching Method: |
| Air |
| Mounting Facility Type And Quantity: |
| 1 plug-in terminal single mounting facility |
| Storage Type: |
| General purpose warehouse |
| Cubic Measure: |
| 0.398 cubic inches |
| Nonpile-up Main Contact Arrangement: |
| 2 pole, double throw, one position momentary |
| Time Delay: |
| 0.005 seconds fixed operate and release time |
| Operating Voltage Rating And Type At Specificationified Temp: |
| 26.0 volts dc 25 degrees celsius single winding |
| Main Contact Load Current Rating At Maximum Rated Voltage: |
| 2.0 amperes ac resistive load and 2.0 amperes dc resistive load |
| Main Contact Maximum Voltage Rating In Volts: |
| 115.0 ac and 28.0 dc |
| Terminal Type And Quantity: |

8 pin all functions

NSN 5945-01-199-5567

Electromagnetic Relay - Page 2 of 2



| _ | | | | - | | |
|---|---|---|-----|---|------|--|
| C | h | Δ | Iŧ. | | ife: | |
| | | | | | | |

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A03300