

View Online at <https://aerobasegroup.com/nsn/5945-01-199-5570>

**Overall Length:**

0.477 inches

**Overall Diameter:**

0.405 inches

**Environmental Protection:**

Hermetic and shock resistant and vibration resistant

**End Application:**

Tarawa class lha; los angeles class ssn (688)

**Winding Quantity:**

1

**Coil Quantity:**

1

**Winding Dc Resistance Rating:**

500.0 ohms single winding

**Duty Type:**

Continuous

**Mounting Facility Type And Quantity:**

1 plug-in terminal single mounting facility

**Features Provided:**

Coil voltage suppression

**Nonpile-up Main Contact Arrangement:**

1 pole, double throw, one position momentary

**Criticality Code Justification:**

Feat

**Time Delay:**

0.0075 seconds fixed release time

**Operating Voltage Rating And Type At Specificationified Temp:**

12.0 volts dc 25 degrees celsius single winding

**Main Contact Load Current Rating At Maximum Rated Voltage:**

2.0 amperes dc resistive load

**Main Contact Maximum Voltage Rating In Volts:**

28.0 dc

**Special Features:**

Transistor driven; weapon system essential

**Terminal Type And Quantity:**

7 pin energizing element and contacts

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A03300