# NSN 5945-01-199-5570

Electromagnetic Relay - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5945-01-199-5570



## **Overall Length:**

0.477 inches

## **Overall Diameter:**

0.405 inches

# **Environmental Protection:**

Hermetic and shock resistant and vibration resistant

### End Application:

Tarawa class lha; los angeles class ssn (688)

#### Winding Quantity:

1

## **Coil Quantity:**

1

### Winding Dc Resistance Rating:

500.0 ohms single winding

Duty Type:

Continuous

### Mounting Facility Type And Quantity:

1 plug-in terminal single mounting facility

## **Features Provided:**

Coil voltage suppression

### Nonpile-up Main Contact Arrangement:

1 pole, double throw, one position momentary

## Criticality Code Justification:

Feat

#### Time Delay:

0.0075 seconds fixed release time

### **Operating Voltage Rating And Type At Specificationified Temp:**

12.0 volts dc 25 degrees celsius single winding

### Main Contact Load Current Rating At Maximum Rated Voltage:

2.0 amperes dc resistive load

### Main Contact Maximum Voltage Rating In Volts:

28.0 dc

## **Special Features:**

Transistor driven; weapon system essential

# Terminal Type And Quantity:

7 pin energizing element and contacts

Shelf Life:

N/a

# Unit Of Measure:

--

## Demilitarization:

No

# NSN 5945-01-199-5570

Electromagnetic Relay - Page 2 of 2

**Fiig:** A03300

