NSN 5945-01-199-5572

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-199-5572

Thread Class: 2a single mounting facility **Thread Direction:** Right-hand single mounting facility **Overall Length:** 3.500 inches Center To Center Distance Between Mounting Facilities Parallel To Length: 2.375 inches single mounting facility Center To Center Distance Between Mounting Facilities Parallel To Width: 2.125 inches single mounting facility **Overall Height:** 3.000 inches **Overall Width:** 3.000 inches **Case Material:** Metal **Environmental Protection:** Hermetic **Fragility Factor:** Moderately rugged **Frequency In Hertz:** 60.0 Winding Quantity: 1 **Purpose For Which Designed:** General **Coil Quantity:** 1 **Duty Type:** Continuous Arc Quenching Method: Air Mounting Facility Type And Quantity: 4 threaded stud single mounting facility Storage Type: General purpose warehouse **Cubic Measure:** 31.500 cubic inches Thready Qty Per Inch (tpi): 32 single mounting facility **Thread Size:**

0.164 inches single mounting facility

NSN 5945-01-199-5572

Electromagnetic Relay - Page 2 of 2



Mounting Facility Pattern: Rectangular single mounting facility **Nonpile-up Main Contact Arrangement:** 1 pole, single throw, normally open, momentary action and 1 pole, single throw, normally closed, momentary action **Time Delay:** 0.05 seconds adjustable operate time and 0.30 seconds adjustable operate time **Operating Voltage Rating And Type At Specificationified Temp:** 208.0 volts ac 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage: 3.0 amperes ac resistive load and 5.0 amperes dc resistive load Main Contact Maximum Voltage Rating In Volts: 120.0 ac and 28.0 dc **Thread Series Designator:** Unc single mounting facility **Terminal Type And Quantity:** 2 threaded stud dummy Shelf Life: N/a Unit Of Measure: ---**Demilitarization:** No Fiig: A03300