NSN 5945-01-199-5574

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-199-5574

view Online at https://aerobasegroup.com/nsn/004-0-01-100-001-4
Thread Class:
2a single mounting facility
Thread Direction:
Right-hand single mounting facility
Overall Length:
3.500 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
2.625 inches single mounting facility
Center To Center Distance Between Mounting Facilities Parallel To Width:
2.125 inches single mounting facility
Overall Height:
4.875 inches
Overall Width:
3.000 inches
Case Material:
Metal
Environmental Protection:
Hermetic
Fragility Factor:
Moderately rugged
Frequency In Hertz:
60.0
Winding Quantity:
1
Purpose For Which Designed:
General
Coil Quantity:
1
Duty Type:
Continuous
Arc Quenching Method:
Air
Mounting Facility Type And Quantity:
4 threaded stud single mounting facility
Storage Type:
General purpose warehouse
Cubic Measure:
51.188 cubic inches
Thready Qty Per Inch (tpi):
32 single mounting facility
Thread Size:

Till Cad Oizc.

0.164 inches single mounting facility

NSN 5945-01-199-5574

Electromagnetic Relay - Page 2 of 2



Mounting Facility Pattern:

Rectangular single mounting facility

Nonpile-up Main Contact Arrangement:

1 pole, single throw, normally open, momentary action and 1 pole, single throw, normally closed, momentary action

Time Delay:

0.05 seconds adjustable operate time and 0.30 seconds adjustable operate time

Operating Voltage Rating And Type At Specificationified Temp:

120.0 volts ac 25 degrees celsius single winding

Main Contact Load Current Rating At Maximum Rated Voltage:

3.0 amperes ac resistive load and 5.0 amperes dc resistive load

Main Contact Maximum Voltage Rating In Volts:

120.0 ac and 28.0 dc

Thread Series Designator:

Unc single mounting facility

Terminal Type And Quantity:

6 threaded stud all functions

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A03300