# NSN 5945-01-199-5579

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-199-5579

# Thread Class: 2a single mounting facility

Thread Direction:

Right-hand single mounting facility

#### **Overall Length:**

1.590 inches

# Center To Center Distance Between Mounting Facilities Parallel To Length:

1.000 inches single mounting facility

#### Center To Center Distance Between Mounting Facilities Parallel To Width:

0.940 inches single mounting facility

#### **Overall Height:**

2.505 inches

#### **Overall Width:**

1.380 inches

#### Case Material:

Metal

# **Environmental Protection:**

Hermetic

### **Fragility Factor:**

Moderately rugged

### Winding Quantity:

1

# **Purpose For Which Designed:**

General

### **Coil Quantity:**

1

### Duty Type:

Continuous

### Arc Quenching Method:

Air

### Mounting Facility Type And Quantity:

4 threaded stud single mounting facility

#### Storage Type:

General purpose warehouse

#### Cubic Measure:

5.496 cubic inches

### Thready Qty Per Inch (tpi):

32 single mounting facility

## Thread Size:

0.132 inches single mounting facility

### Mounting Facility Pattern:

Rectangular single mounting facility

# NSN 5945-01-199-5579

Electromagnetic Relay - Page 2 of 2



Nonpile-up Main Contact Arrangement: 2 pole, double throw, one position momentary Time Delay: 80.00 seconds fixed operate time **Operating Voltage Rating And Type At Specificationified Temp:** 24.0 volts dc 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage: 10.0 amperes dc resistive load Main Contact Maximum Voltage Rating In Volts: 28.0 dc **Thread Series Designator:** Unc single mounting facility Terminal Type And Quantity: 8 wire hook all functions Shelf Life: N/a Unit Of Measure: ---**Demilitarization:** No Fiig: A03300