NSN 5945-01-200-3380

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-200-3380

view Online at https://aerobasegroup.com/nsn/5945-01-200-3360
Thread Class:
2a single mounting facility
Thread Direction:
Right-hand single mounting facility
Overall Length:
1.590 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
1.000 inches single mounting facility
Center To Center Distance Between Mounting Facilities Parallel To Width:
0.940 inches single mounting facility
Overall Height:
2.505 inches
Overall Width:
1.380 inches
Case Material:
Metal
Environmental Protection:
Hermetic
Fragility Factor:
Moderately rugged
Winding Quantity:
1
Purpose For Which Designed:
General
Coil Quantity:
1
Duty Type:
Continuous
Arc Quenching Method:
Air
Mounting Facility Type And Quantity:
4 threaded stud single mounting facility
Storage Type:
General purpose warehouse
Cubic Measure:
5.496 cubic inches
Thready Qty Per Inch (tpi):
32 single mounting facility
Thread Size:
0.132 inches single mounting facility
Mounting Facility Pattern:

Rectangular single mounting facility

NSN 5945-01-200-3380

Electromagnetic Relay - Page 2 of 2



Nonpile-up	Main	Contact	Arrand	ement:

2 pole, double throw, one position momentary

Time Delay:

30.00 seconds fixed release time

Operating Voltage Rating And Type At Specificationified Temp:

24.0 volts dc 25 degrees celsius single winding

Main Contact Load Current Rating At Maximum Rated Voltage:

10.0 amperes dc resistive load

Main Contact Maximum Voltage Rating In Volts:

28.0 dc

Thread Series Designator:

Unc single mounting facility

Terminal Type And Quantity:

8 wire hook all functions

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A03300