# NSN 5945-01-200-6313

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-01-200-6313

# **Overall Length:**

0.280 inches

**Overall Diameter:** 

0.370 inches

# **Case Material:**

Metal

# **Environmental Protection:**

Hermetic

#### Fragility Factor:

Moderately rugged

#### **End Application:**

Radar set

### Winding Quantity:

1

# **Purpose For Which Designed:**

. General

Coil Quantity:

1

# Winding Dc Resistance Rating:

2.5 kilohms single winding

## **Duty Type:**

Continuous

### Arc Quenching Method:

Air

# Mounting Facility Type And Quantity:

1 terminal single mounting facility

### Storage Type:

General purpose warehouse

### Nonpile-up Main Contact Arrangement:

2 pole, double throw, one position momentary

### Criticality Code Justification:

Feat

# Time Delay:

0.002 seconds fixed operate time

# Operating Voltage Rating And Type At Specificationified Temp:

30.0 volts dc 25 degrees celsius single winding

# Main Contact Load Current Rating At Maximum Rated Voltage:

100.0 milliamperes dc lamp load

# Main Contact Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

# **Special Features:**

Failure rate level 0.1 percent

# NSN 5945-01-200-6313

Electromagnetic Relay - Page 2 of 2



### **Test Data Document:**

81349-mil-r-39016 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Terminal Type And Quantity:
8 wire lead all functions
Specification Data:
81349-mil-r-39016/9 government specification
Shelf Life:
N/a
Unit Of Measure:
-Demilitarization:
No
Fig:
A03300