

View Online at <https://aerobasegroup.com/nsn/5945-01-200-8520>

**Thread Class:**

2a single mounting facility

**Overall Length:**

1.015 inches

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

0.687 inches single mounting facility

**Overall Height:**

1.422 inches

**Overall Width:**

1.015 inches

**Environmental Protection:**

Hermetic and shock resistant and vibration resistant

**Winding Quantity:**

1

**Coil Quantity:**

1

**Winding Dc Resistance Rating:**

290.0 ohms single winding

**Duty Type:**

Continuous

**Mounting Facility Type And Quantity:**

3 threaded stud single mounting facility

**Features Provided:**

Coil voltage suppression

**Thready Qty Per Inch (tpi):**

32 single mounting facility

**Thread Size:**

0.138 inches single mounting facility

**Mounting Facility Pattern:**

Triangle single mounting facility

**Nonpile-up Main Contact Arrangement:**

4 pole, double throw, one position momentary

**Time Delay:**

0.015 seconds fixed operate and release time

**Center To Center Distance Between Mounting Facilities Parallel To The Altitude Of An Isosceles Triangle:**

0.687 inches single mounting facility

**Operating Voltage Rating And Type At Specificationified Temp:**

28.0 volts dc 25 degrees celsius single winding

**Main Contact Load Current Rating At Maximum Rated Voltage:**

2.5 amperes ac resistive load and 12.0 amperes dc resistive load

**Main Contact Maximum Voltage Rating In Volts:**

200.0 ac and 28.0 dc

**Thread Series Designator:**

Unc single mounting facility

**Terminal Type And Quantity:**

14 pin all functions

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A03300